

Add-on modules DX³

for 1 module/pole DX³ MCBs



4 104 01



4 104 71



4 105 55

Technical characteristics [see e-catalogue](#)

Conform to IEC 61009-1, IEC 62423 (F type)

Voltage independent tripping except Cat.No 4 106 57/58/59

• AC type : detect AC components faults

• A type : detect AC and DC component faults

• F type (High immunity) : detect faults with AC and DC components, increased immunity to false tripping

Detection of high frequency fault currents

For mounting on the right-hand side of 1 module per pole DX³ MCBs

Pack	Cat.Nos	2-pole - 230 V _~		
		AC Type		
		Sensitivity (mA)	Nominal rating In (A)	Number of modules
1	4 104 01	30	40	2
1	4 104 02	30	63	2
1	4 104 13	300	40	2
1	4 104 14	300	63	2
1	4 104 24	300 selective	63	2
1	4 104 26	1000 selective	63	2
		A Type		
1	4 104 28	30	40	2
1	4 104 29	30	63	2
1	4 104 31	300	40	2
1	4 104 32	300	63	2
		F type (old Hpi type)		
1	4 104 35	30	63	2

Pack	Cat.Nos	3-pole - 400 V _~		
		AC Type		
		Sensitivity (mA)	Nominal rating In (A)	Number of modules
1	4 104 71	30	40	3
1	4 104 72	30	63	3
1	4 104 74	300	40	3
1	4 104 75	300	63	3
1	4 104 77	300 selective	63	3
		A Type		
1	4 104 80	30	63	3
1	4 104 83	300	63	3
		F type (old Hpi type)		
1	4 104 86	30	63	3

Pack	Cat.Nos	4-pole - 400 V _~		
		AC Type		
		Sensitivity (mA)	Nominal rating In (A)	Number of modules
1	4 104 99	30	40	3
1	4 105 00	30	63	3
1	4 105 11	300	40	3
1	4 105 12	300	63	3
1	4 105 21	300 selective	63	3
1	4 105 23	1000 selective	63	3
		A Type		
1	4 105 25	30	40	3
1	4 105 26	30	63	3
1	4 105 28	300	40	3
1	4 105 29	300	63	3
1	4 105 31	300 selective	63	3
		F type (old Hpi type)		
1	4 105 34	30	63	3
1	4 105 55	300 selective	63	3