



Technical characteristics p. 254

**Metal doors for XL<sup>3</sup> S 630 cable sleeves**

Pack	Cat.Nos	Description
		Supplied with fixed handle Key barrel to be ordered separately 2 or 3 locking points (depending on door height) For cable sleeves with faceplate height (mm)
1	3 376 40	750
1	3 376 50	900
1	3 376 60	1050
1	3 376 70	1200
1	3 376 80	1350
1	3 376 90	1500
1	3 377 00	1650
1	3 377 10	1800
1	3 377 20	1950
1	3 377 30	2100
1	3 377 40	2250

Pack	Cat.Nos	Description
1	3 397 11	For XL <sup>3</sup> S 630 with faceplate height 750 to 1200 mm
1	3 397 12	For XL <sup>3</sup> S 630 with faceplate height 1350 to 2250 mm
1	3 397 16	Locking handle no. 405 for XL <sup>3</sup> S 630 with faceplate height 750 to 1200 mm Supplied with a set of 2 keys
1	3 397 17	Locking handle no. 405 for XL <sup>3</sup> S 630 with faceplate height 1350 to 2250 mm Supplied with a set of 2 keys

**Faceplate for cable sleeves**

**For external cable sleeves**

Pack	Cat.Nos	Description
		For cable sleeves with faceplate height (mm)
1	3 378 82	750
1	3 378 84	900
1	3 378 86	1050
1	3 378 88	1200
1	3 378 90	1350
1	3 378 92	1500
1	3 378 94	1650
1	3 378 96	1800
1	3 378 98	1950
1	3 379 00	2100
1	3 379 02	2250

**For internal cable sleeves**

Pack	Cat.Nos	Description
1	3 379 12	750
1	3 379 13	900
1	3 379 14	1050
1	3 379 15	1200
1	3 379 16	1350
1	3 379 17	1500
1	3 379 18	1650
1	3 379 19	1800
1	3 379 20	1950
1	3 379 21	2100
1	3 379 22	2250

**Wall mounting**

1	3 379 52	Set of 4 lugs for wall mounting
---	----------	---------------------------------

**Functional uprights for external cable sleeves**

Pack	Cat.Nos	Description
		For fixing equipment in external cable sleeves For cable sleeves with faceplate height (mm)
1	3 379 86	750
1	3 379 87	900
1	3 379 88	1050
1	3 379 89	1200
1	3 379 90	1350
1	3 379 91	1500
1	3 379 92	1650
1	3 379 93	1800
1	3 379 94	1950
1	3 379 95	2100
1	3 379 96	2250

**Plinths for XL<sup>3</sup> S 630 and 4000 enclosures**

Pack	Cat.Nos	Description
		Height 100 mm
1	3 382 00	<b>Corner pieces for plinth</b> Set of 4 corner pieces
		<b>Finishing panel for plinth</b> Set of 2 plates Length (mm)
1	3 382 05	300
1	3 382 01	350
1	3 382 02	450
1	3 382 03	600
1	3 382 04	800

**Joining kits**

1	3 379 50	For connecting two enclosures Joining screws for XL <sup>3</sup> S 630 and 4000 enclosures
1	3 379 49	Joining plates for XL <sup>3</sup> S 630 and 4000 enclosures (to be used to strengthen joining)

**Seal for IP 43 protection**

1	3 379 51	Supplied ready to use for XL <sup>3</sup> S 630 enclosures
---	----------	---

**IP 30 finishing kits**

Set of 2 finishing pieces  
Allow 1 horizontal kit and 1 vertical kit per enclosure

**Finishing kits - vertical mounting**

Pack	Cat.Nos	Description
		For enclosures with faceplate height (mm)
1	3 379 60	750
1	3 379 61	900
1	3 379 62	1050
1	3 379 63	1200
1	3 379 64	1350
1	3 379 65	1500
1	3 379 66	1650
1	3 379 67	1800
1	3 379 68	1950
1	3 379 69	2100
1	3 379 70	2250

**Finishing kits - horizontal mounting**

1	3 379 72	For 16-module enclosures
1	3 379 73	For 24-module enclosures
1	3 379 74	For 36-module enclosures
1	3 379 71	For cable sleeves