


Equipment for XL³ 4000

for mounting on adjustable plates: DPX³ 630 fixed version





0 208 20



0 208 23

Adjustable plates are used for front terminal/rear terminal connection and mounting of motor-driven or rotary handles


Pack	Cat.Nos	
		Fixing fixed version DPX³ 630, with front or rear terminals
		Adjustable fixing devices for MCCBs in vertical position
	24 modules 36 modules	The MCCBs are fixed using special plates
1	0 207 20	For 1 to 3 DPX ³ 630
1	0 207 22 0 207 72	For 1 to 3 DPX ³ 630 with earth leakage module
		Mounting plates for devices in vertical position
	24 modules	DPX ³ 630
1	0 207 85	DPX ³ 630 with earth leakage module
		Adjustable plates for devices in horizontal position
	24 modules	For 1 DPX ³ 630 with or without elcbs
1	0 207 93	
		Metal faceplates for devices in vertical position
		For 1 to 3 DPX³ 630 only
	24 modules 36 modules	1/4 turn
1	0 208 20 ¹	With captive screws
1	0 209 20 ² 0 209 70 ²	
		For 1 to 3 DPX³ 630 with downstream elcbs
		1/4 turn
1	0 208 22 ¹	With captive screws
1	0 209 22 ² 0 209 72 ²	
		Metal faceplates for devices in horizontal position
		For 1 DPX³ 630 with or without elcbs
		1/4 turn
	24 modules	With captive screws
1	0 208 23 ¹	
1	0 209 21 ²	
		For 1 DPX³ 630 with or without elcbs with motor-driven or rotary handle
		With captive screws
1	0 209 23 ²	



1: For fastening and sealing
2: Hinges Cat.No 0 209 59 available as an option

Equipment for XL³ 4000 for mounting on adjustable

plates: DPX³ 630 plug-in, draw-out version or automatic transfer switches



0 210 60



0 210 62

Adjustable plates are used for front terminal/rear terminal connection and mounting of motor-driven or rotary handles

Pack	Cat.Nos	
		Fixing plug-in or draw-out version DPX³ 630, with front or rear terminals
		Adjustable fixing devices for MCCBs in vertical position
		The MCCBs are fixed using special plates
1	0 210 60	For 1 to 2 DPX ³ 630
1	0 210 61	For 1 to 2 DPX ³ 630 with elcbs
		Mounting plates for devices in vertical position
		For device only
1	0 210 62	For device with elcbs
1	0 210 63	For plug-in or draw-out device with or without elcbs
		Metal faceplates for plug-in devices
		Faceplates with hinges and lock
		Devices in vertical position
1	0 210 64	For 1 to 2 DPX ³ 630
1	0 210 65	For 1 to 2 DPX ³ 630 with elcb
		Devices in horizontal position
1	0 212 17	For device with or without elcbs
		Metal faceplates for draw-out devices
		Faceplates with hinges and lock
		Devices in vertical position with or without rotary handle
1	N 0 210 70	For 1 DPX ³ 630 without elcb
1	0 210 71	For 1 DPX ³ 630 with elcb
		Devices in vertical position with motor-driven handle
1	0 210 72	For 1 device without elcb
		Devices in horizontal position
1	0 212 18	For 1 device with or without downstream earth leakage module with or without rotary handle
1	0 212 19	For 1 device with or without elcbs mounted underneath with motor-driven handle
		Fixing automatic transfer switches DPX³ 630
		Devices in vertical position
1	0 210 66	For 2 fixed or draw-out devices
		Devices in horizontal position
1	N 0 210 73	For 2 fixed or draw-out devices
		Metal faceplates for automatic transfer switches
		For fixed version DPX³ 630
		With captive screws
		For 2 devices with or without motor-driven handle
1	0 210 67	Devices in vertical position
		For draw-out DPX³ 630 in vertical position
		With hinges and lock
1	0 210 68	For 2 devices
1	0 210 69	For 2 devices with motor-driven handle
		For draw-out DPX³ 630 in horizontal position
		For 2 devices
1	N 0 210 74	For 2 devices with motor-driven handle
1	0 210 75	