

# Plexo<sup>3</sup>

## IP 65 weatherproof cabinets, multifunction sleeves and accessories



Technical characteristics **p. 287**

Self-extinguishing; resistance to incandescent wire 650°C. Allows to achieve assemblies conform to IEC 61 439 - 3

Weatherproof cabinets - IP 65 - IK 09 - Class II

Door and cabinet fully reversible. Removable chassis and faceplates from 2-row versions up

2-position rail for modular products and moulded cases. Spacing between rails 150 mm

Can be fitted with perforated plates and solid faceplates for mounting non-modular products

Lockable door handle, sealable cover and faceplate. Shock-resistant polystyrene material

Box colour light grey L750A, cover colour dark grey R746A. Supplied without terminal blocks

Pack	Cat.Nos	Cabinets 2 to 8 modules	
6	6 019 32	Number of rows	Number of modules
6	6 019 94	1	2 (+1)
6	6 019 96	1	4
6	6 019 98	1	6
6	6 019 98	1	8

  

Pack	Cat.Nos	Cabinets 12 modules per row	
1	6 018 31	Number of rows	
1	6 018 32	1	
1	6 018 32	2	
1	6 018 33	3	

  

Pack	Cat.Nos	Cabinets 18 modules per row	
1	6 018 35	Number of rows	
1	6 018 36	1	
1	6 018 36	2	
1	6 018 37	3	
1	6 018 38	4	

  

Pack	Cat.Nos	Multifunction sleeves	
		Supplied with hinges connecting the cover to the back of the cabinet	
		For use with 12 and 18-module cabinets using joining kit Cat.No 0 019 67	
		Can be fitted with control units and accessories: P17 16 A and 32 A sockets with standard fixing centres, flush-mounted IP 55 Plexo wiring accessories, Osmoz, modular rail at the back of the box	
1	0 019 17	<b>Vertical</b>	
1	0 019 18	For 2 rows cabinets	
1	0 019 18	For 3 rows cabinets	

Pack	Cat.Nos	Accessories	
5	0 019 71	<b>Plexo adaptor</b> For fixing Plexo flush mounting wiring accessories, complete version (p. 602) on Plexo <sup>3</sup> cabinets (minimum 2 rows)	
		<b>Installation supports for terminal blocks</b> Set of 2 supports for mounting additional terminal blocks (p. 200) or empty supports for screw terminal blocks (p. 200) into Plexo <sup>3</sup> cabinets	
1	0 019 72	For 1 and 2 rows cabinets, 12 and 18 modules per row	
1	0 019 73	For 3 and 4 rows cabinets, 12 and 18 modules per row	
1	0 019 66	<b>Key lock</b> N° 850	
1	0 019 67	<b>Joining kit</b> Allows cables to be run horizontally or vertically between 2 cabinets or multifunction sleeves while maintaining IP 65 protection	
1	0 019 68	<b>Sealing kit</b> Set of 2 sealable terminal shields for cover and 8 sealable supports for faceplate	
1	0 019 69	<b>Fixing lugs</b> Set of 4 wall mounting lugs for Plexo <sup>3</sup> boxes and P 17 combined units (p. 386)	
20	0 019 61	<b>Blanking plates</b> 5, separable into modules or 1/2 module Grey R746A	
1	0 019 55	<b>Direct piercing end caps</b> Pack consisting of 2 Ø32 mm ISO end caps, 5 Ø25 mm ISO end caps and 10 Ø20 mm ISO end caps	
1	<b>N</b> 0 019 56	Pack consisting of 100 Ø20 mm ISO end caps	
1	0 019 57	Pack consisting of 100 Ø25 mm ISO end caps	
1	0 019 58	Pack consisting of 100 Ø32 mm ISO end caps	
		<b>Plain faceplates</b>	
2	0 019 64	For 12 modules cabinets	
2	0 019 65	For 18 modules cabinets	
		<b>Perforated plates</b>	
		Allow the DIN rail to be replaced with a LINA 25 plate when integrating non-modular products	
2	0 019 62	For 12 modules cabinets, Height 150 mm	
2	4 018 53	For 18 modules cabinets, Height 150 mm	
		<b>Hinges</b>	
2	0 019 70	Set of 2 hinges connecting the back of the cabinet to the cover	

IP 2X terminal blocks, and empty supports **p. 200**

