

Heat regulation for cabinets and enclosures

ventilators (continued)



0 365 74



0 348 08



0 365 77



0 365 79



0 348 05



0 348 35



Technical characteristics **see e-catalogue**

Pack	Cat.Nos	Air circulation kit 160 m³/h															
1	0 365 74	230 V~ - 50/60 Hz Uniformizes temperature in enclosure Prevent hot spots Plate or rail mounting in bottom part of enclosure or under most sensitive equipment The air flow must be directed upward															
		Roof ventilators															
		Plastic - RAL 7035 Provide very high extraction rate Screw mounting on top of enclosures Dimensions: 400 x 350 x 100 mm Delivered without input air louvre IP 23 - IK 08 With motor															
		<table border="1"> <thead> <tr> <th>Free blowing (m³/h)</th> <th>Flow rate (m³/h) with 1 louvre Cat.No 0 348 35</th> <th>Flow rate (m³/h) with 2 louvres Cat.No 0 348 35</th> <th>Flow rate (m³/h) with 1 louvre Cat.No 0 348 36</th> <th>Flow rate (m³/h) with 2 louvres Cat.No 0 348 36</th> </tr> </thead> <tbody> <tr> <td>600</td> <td>350</td> <td>400</td> <td>400</td> <td>450</td> </tr> <tr> <td>1000</td> <td>400</td> <td>500</td> <td>500</td> <td>600</td> </tr> </tbody> </table>	Free blowing (m ³ /h)	Flow rate (m ³ /h) with 1 louvre Cat.No 0 348 35	Flow rate (m ³ /h) with 2 louvres Cat.No 0 348 35	Flow rate (m ³ /h) with 1 louvre Cat.No 0 348 36	Flow rate (m ³ /h) with 2 louvres Cat.No 0 348 36	600	350	400	400	450	1000	400	500	500	600
Free blowing (m ³ /h)	Flow rate (m ³ /h) with 1 louvre Cat.No 0 348 35	Flow rate (m ³ /h) with 2 louvres Cat.No 0 348 35	Flow rate (m ³ /h) with 1 louvre Cat.No 0 348 36	Flow rate (m ³ /h) with 2 louvres Cat.No 0 348 36													
600	350	400	400	450													
1000	400	500	500	600													
1	0 348 07	600															
1	0 348 08	1000															

Pack	Cat.Nos	Natural ventilation
2	0 365 77	IP 66 - IK 08 ventilation glands for cabinets Polyamide PA 6 - RAL 7035 Drilling Ø40.5 mm
2	0 365 78	IP 44 - IK 08 ventilation glands for cabinets For outdoor use Grey polyamide 6.6 Drilling Ø15 mm
2	0 365 79	Drilling Ø30.5 mm
		Metal louvres
		IP 32 - IK 10
1	0 348 04	Set of 2 metal louvres + 2 anti-insect grilles RAL 7035 - 138 x 138 mm
1	0 348 05	RAL 7035 - 248 x 248 mm
		Plastic louvres
		RAL 7035
		Supplied singly
1	0 348 34	IP 44 - 150 x 150 mm
1	0 348 35	IP 54 - 250 x 250 mm
1	0 348 36	IP 54 - 325 x 325 mm



Exchangers, air conditioners,
Please, consult us

