

Plastic cable glands IP 55

ISO and PG



Pack	Cat.Nos	Grey RAL 7035 cable glands		
		Cable gland with flexible blades designed for commercial applications that require IP 55 protection and a good hold on the cables		
		ISO		
		Conform to EN 50262		
			Clamping capacity	
		ISO	Ø Min. (mm)	Ø Max. (mm)
50	0 968 00	12	4	6.5
50	0 968 01	16	5	10
50	0 968 03	20	10	14
50	0 968 05	25	13	18
25	0 968 06	32	18	25
10	0 968 07	40	22	32
10	0 968 08	50	30	38
10	0 968 09	63	34	44
		PG		
		Conform to UTE C 68-300 and 68-311 guides recommendations		
			Clamping capacity	
		PG	Ø Min. (mm)	Ø Max. (mm)
50	0 968 20	7	3.5	6
50	0 968 21	9	4	8
50	0 968 22	11	5	10
50	0 968 23	13.5	7	12
50	0 968 24	16	10	14
50	0 968 25	21	13	18
25	0 968 26	29	18	25
10	0 968 27	36	22	32
10	0 968 28	42	30	38
10	0 968 29	48	34	44

Pack	Cat.Nos	Grey RAL 7035 locking nuts		
		ISO		
50	3 868 81	M 12 x 1.5		
50	3 868 82	M 16 x 1.5		
50	3 868 83	M 20 x 1.5		
50	3 868 84	M 25 x 1.5		
25	3 868 85	M 32 x 1.5		
25	3 868 86	M 40 x 1.5		
10	3 868 87	M 50 x 1.5		
10	3 868 88	M 63 x 1.5		
		PG		
50	3 868 71	PG 7		
50	3 868 72	PG 9		
50	3 868 73	PG 11		
50	3 868 74	PG 13.5		
50	3 868 75	PG 16		
50	3 868 76	PG 21		
25	3 868 77	PG 29		
10	3 868 78	PG 36		
10	3 868 79	PG 42		
10	3 868 80	PG 48		

RTA conduit system brochure available on request



Plastic cable glands IP 55

ISO and PG

Cable glands

Characteristics

Halogen-free polyamide UL 94-V2
 Operating temperature: - 20 °C to + 80 °C
 Self-extinguishing 650 °C according to IEC 60695-2-11

Dimensions (mm)

ISO

Cat.Nos	Threading	A max.	B	Ø D	C to flat	Ø E	Drilling Ø
0 968 00	ISO 12	23	8	19	16	11.8	12.7
0 968 01	ISO 16	28	15	25	22	15.8	16.2
0 968 03	ISO 20	34	15	29	26	19.9	20.4
0 968 05	ISO 25	36	15	35	30	24.8	25.4
0 968 06	ISO 32	40	15	46	42	31.6	32.5
0 968 07	ISO 40	47	18	53	52	39.8	40.5
0 968 08	ISO 50	48	18	65	58	49.8	50.8
0 968 09	ISO 63	55	18.5	71	66	62.6	64


PG

Cat.Nos	Threading	A max.	B	Ø D	C to flat	Ø E	Drilling Ø
0 968 20	PG 7	23	8	17	15	12.1	12.7
0 968 21	PG 9	27	8	22	19	15.1	15.2
0 968 22	PG 11	31	8	25	22	18.2	18.6
0 968 23	PG 13.5	32	9	27	24	20.2	20.4
0 968 24	PG 16	32	10	29	27	22.3	22.5
0 968 25	PG 21	35	11	39	33	28.1	28.3
0 968 26	PG 29	41	11	46	42	36.9	37
0 968 27	PG 36	50	14.5	59	53	46.4	47
0 968 28	PG 42	52	14.5	66	59	53.5	54
0 968 29	PG 48	52	15.5	70	64	59.9	60

Locking nuts

Glass fiber polyamide

Dimensions (mm)



ISO

Cat.Nos	Threading	C1 to flat	E	Ø D1
3 868 81	M 12	17	5	19
3 868 82	M 16	22	5	24
3 868 83	M 20	26	6	28
3 868 84	M 25	32	6	35
3 868 85	M 32	42	7	46
3 868 86	M 40	50	7	56
3 868 87	M 50	60	8	66
3 868 88	M 63	75	8	81

PG

Cat.Nos	Threading	C1 to flat	E	Ø D1
3 868 71	PG 7	19	5	21
3 868 72	PG 9	22	5	24
3 868 73	PG 11	24	5	26
3 868 74	PG 13.5	26	6	28
3 868 75	PG 16	32	6	35
3 868 76	PG 21	36	7	38
3 868 77	PG 29	46	7	51
3 868 78	PG 36	60	8	66
3 868 79	PG 42	64	8	72
3 868 80	PG 48	69	8	77