

Transcab cable ducting



6 362 02



6 362 08



6 361 17



6 361 25



Approvals **p. 919**
 Technical characteristics **p. 349**

6.5 mm wide fingers with a 6 mm spacing
 Accepts up to 6 mm² without breaking side wall finger
 Two pre-scored lines allow removal of fingers
 Bump on side wall fingers help cabling
 Rounded fingers prevent injury during cabling
 Conform to EN 500 85 parts 2 and 3
 Plastic cable ducting (base + cover)
 Side perforations at intervals of 12.5 mm
 Length: 2 m

Pack	Cat.Nos	Light grey halogen free	
		PC/ABS	
		Width x Height (mm)	Capacity (mm ²)
60 ¹	6 362 00	25 x 25	391
56 ¹	6 362 01	25 x 40	720
56 ¹	6 362 02	25 x 60	1159
48 ¹	6 362 06	40 x 40	1245
48 ¹	6 362 07	40 x 60	2007
40 ¹	6 362 08	40 x 80	2717
32 ¹	6 362 12	60 x 60	3115
32 ¹	6 362 13	60 x 80	4216
24 ¹	6 362 17	80 x 80	5715
16 ¹	6 362 25	120 x 80	8729

1: Number of meters in pack

Pack	Cat.Nos	Grey RAL 7030	
		PVC	
		Width x Height (mm)	Capacity (mm ²)
32 ¹	6 360 95	15 x 25	264
40 ¹	6 360 96	15 x 40	455
60 ¹	6 361 00	25 x 25	391
56 ¹	6 361 01	25 x 40	720
56 ¹	6 361 02	25 x 60	1159
40 ¹	6 361 03	25 x 80	1600
56 ¹	6 361 05	40 x 25	692
48 ¹	6 361 06	40 x 40	1245
48 ¹	6 361 07	40 x 60	2007
40 ¹	6 361 08	40 x 80	2717
24 ¹	6 361 09	40 x 100	3354
32 ¹	6 361 11	60 x 40	1932
32 ¹	6 361 12	60 x 60	3115
32 ¹	6 361 13	60 x 80	4216
24 ¹	6 361 14	60 x 100	5216
24 ¹	6 361 15	80 x 40	2647
24 ¹	6 361 16	80 x 60	4200
24 ¹	6 361 17	80 x 80	5715
20 ¹	6 361 18	80 x 100	7078
24 ¹	6 361 19	100 x 40	3363
24 ¹	6 361 20	100 x 60	5307
16 ¹	6 361 21	100 x 80	7215
16 ¹	6 361 22	100 x 100	8960
16 ¹	6 361 24	120 x 60	6403
16 ¹	6 361 25	120 x 80	8729
12 ¹	6 361 23	150 x 100	13683

1: Number of meters in pack



Accessories,
p. 348

