


Green'up™ sockets and charging stations

for electric vehicles and plug-in hybrids

	IP	IK	Charging mode	Power (kW)	Number of charging points	Wall mounting	Free standing	Options		Average charging time (in hours) depending on the vehicle and battery type			
								Communication kit	RFID reader (Used with communication kit Cat.No 0 590 56)	Vehicle battery capacity			
										15/16 kW/h	22/24 kW/h	30/32 kW/h	
SINGLE-PHASE SOCKETS - 230 V													
	Plastic	55	08	Mode 2 ☺	3,7	1	0 904 70 ⁽¹⁾ 0 904 72	-	-	-	5 ⁽²⁾	7 ⁽²⁾	-
	Metal	55	10	Mode 2 ☺	3,7	1	0 778 56	-	-	-	5 ⁽²⁾	7 ⁽²⁾	-
	Metal with key	55	10										
SINGLE-PHASE CHARGING STATIONS - 230 V													
	Plastic	44	08	Mode 3 ☺☺☺	3,7 / 4,6	1	0 590 00	0 590 00 + 0 590 52	0 590 56	-	4	6	8
					7,4	1	0 590 01	0 590 01 + 0 590 52	0 590 56	-	2,5	3,5	4,5
	Plastic	44	08	Modes 2 and 3 ☺☺☺	3,7 / 4,6	1	0 590 30	0 590 30 + 0 590 52	0 590 56	-	4	6	8
					7,4	1	0 590 35	0 590 35 + 0 590 52	0 590 56	-	2,5	3	4,5
	Metal	55	10	Modes 2 and 3 ☺☺☺	3,7 / 4,6	1	0 590 41 + 0 590 53	0 590 41 + 0 590 54	0 590 56	0 590 59 + 0 590 56	4	6	8
						2	0 590 42 + 0 590 53	0 590 42 + 0 590 54	0 590 56	0 590 59 + 0 590 56	4	6	8
		55	10	Modes 2 and 3 ☺☺☺	7,4	1	0 590 43 + 0 590 53	0 590 43 + 0 590 54	0 590 56	0 590 59 + 0 590 56	2,5	3	4,5
						2	0 590 44 + 0 590 53	0 590 44 + 0 590 54	0 590 56	0 590 59 + 0 590 56	2,5	3	4,5
THREE-PHASE CHARGING STATIONS - 400 V													
	Plastic	44	08	Mode 3 ☺☺☺	22	1	0 590 02	0 590 02 + 0 590 52	0 590 56	-	1	1	2
	Metal	55	10	Modes 2 and 3 ☺☺☺	22	1	0 590 48 + 0 590 53	0 590 48 + 0 590 54	0 590 56	0 590 59 + 0 590 56	1	1	2
						2	0 590 49 + 0 590 53	0 590 49 + 0 590 54	0 590 56	0 590 59 + 0 590 56	1	1	2

1: Ready to install version, supplied with RCBO

2: For vehicles with cable equipped with Legrand Green'up plug