

P17 Tempra combined units to be composed

- IK 08 according to IEC 62262
- Self-extinguishing: 650 °C
- Max. IP 66
- RAL 7035

**Example of combined unit configuration**

base + MCCBs, RCDs + faceplate + sockets = combined unit

Bases and faceplates dimensions p. 388

0 577 04 with emergency stop button, appliance inlet and interlocked switched sockets

0 577 20 with interlocked switched sockets

0 577 43 foldable frame equipped with a P 17 worksite combined unit (p. 385)

COMBINED UNITS HEIGHT 220 MM TO 441 MM

**BASES FOR 220 x 125 MM FACEPLATES - MAX IP 66**

Surface mounting box	Base up to 2 sockets 16 A	Base up to 4 sockets 16 A	Base up to 6 sockets 16 A
220 x 125 mm <sup>(4)</sup>	371 x 125 mm <sup>(4)</sup> Rail 5 modules 17.5 mm	441 x 265 mm <sup>(4)</sup> Rail 12 modules 17.5 mm	441 x 405 mm <sup>(4)</sup> Rail 18 modules 17.5 mm
Pack	Pack	Pack	Pack
Cat.No	Cat.No	Cat.No	Cat.No
1	0 577 10	1	0 589 38

**220 X 125 MM FACEPLATES**

1 socket 16 or 32 A	2 sockets 16 A	1 socket 63 A	Plain plate
Pack	Pack	Pack	Pack
Cat.No	Cat.No	Cat.No	Cat.No
5	0 577 12	5	0 577 13 <sup>(1)</sup>

**EXAMPLE OF SOCKETS**

ELV (p. 383)	IP 44
20/25 V~	16 A 2P 0 552 45
	32 A 2P 0 552 95
Domestic pin (p. 383)	IP 54 <sup>(3)</sup>
250 V	16 A 2P+E 0 576 72/76
LV (p. 382)	IP 44 : IP 66-67
200/250 V~	16 A 2P+E 5 551 84 : 5 553 84
	32 A 2P+E 5 552 84 : 5 554 84
	63 A 2P+E - : 5 555 84
380/415 V~	16 A 3P+E 5 551 88 : 5 553 88
	3P+N+E 5 551 89 : 5 553 89
	32 A 3P+E 5 552 88 : 5 554 88
	3P+N+E 5 552 89 : 5 554 89
	63 A 3P+E - : 5 555 88
	3P+N+E - : 5 555 89

**Examples of most common combinations with bases for 220 x 125 mm faceplates**

Base	Total number of sockets on the base	Socket combination	Face plate according to the socket intensity		
			16 A	32 A	63 A
0 577 10 or 0 589 38	1	1 x 16 A or 1 x 32 A or 1 x 63 A	0 577 12	0 577 12	0 577 17
	2	2 x 16 A	0 577 13	-	-
0 577 05	2	2 x 16 A or 2 x 32 A or 2 x 63 A	0 577 12 x 2	0 577 12 x 2	0 577 17 x 2
		1 x 16 A + 1 x 32 A	0 577 12	0 577 12	-
	3	1 x 16 or 32 A + 1 x 63 A	0 577 12	-	0 577 17
0 577 06	3	3 x 16 A	0 577 12 + 0 577 13	-	-
		2 x 16 A + 1 x 32 A	0 577 13	0 577 12	-
	4	2 x 16 A + 1 x 63 A	0 577 13	-	0 577 17
		4 x 16 A	0 577 13 x 2	-	-
0 577 06	3	3 x 16 A or 3 x 32 A or 3 x 63 A	0 577 12 x 3	0 577 12 x 3	0 577 17 x 3
		1 x 16 or 32 A + 2 x 63 A	0 577 12	-	0 577 17 x 2
	4	2 x 16 or 32 A + 1 x 63 A	0 577 12 x 2	-	0 577 17
		2 x 16 A + 1 x 32 A + 1 x 63 A	0 577 13	0 577 12	0 577 17
	5	2 x 16 A + 2 x 32 A	0 577 13	0 577 12 x 2	-
		2 x 16 A + 2 x 63 A	0 577 13	-	0 577 17 x 2
6	4 x 16 A + 1 x 32 A	0 577 13 x 2	0 577 12	-	
	4 x 16 A + 1 x 63 A	0 577 13 x 2	-	0 577 17	
6	16 A	0 577 13 x 3	-	-	

COMBINED UNITS HEIGHT 280 MM TO 501 MM

**BASES FOR 280 x 125 MM FACEPLATES - MAX IP 66**

Surface mounting box	Base up to 3 sockets 16 A	Base up to 6 sockets 16 A	Base up to 9 sockets 16 A
280 x 125 mm <sup>(4)</sup>	421 x 125 mm <sup>(4)</sup> Rail 5 modules 17.5 mm	501 x 265 mm <sup>(4)</sup> Rail 12 modules 17.5 mm	501 x 405 mm <sup>(4)</sup> Rail 18 modules 17.5 mm
Pack	Pack	Pack	Pack
Cat.No	Cat.No	Cat.No	Cat.No
3	0 577 11	1	0 577 20

**280 x 125 MM FACEPLATE**

2 sockets 16 or 32 A	2 interlocked switched sockets 16 A (p. 342)	1 socket 16 or 32 A and 1 socket 63 A	3 sockets 16 A <sup>(2)</sup>	Plain plate
Pack	Pack	Pack	Pack	Pack
Cat.No	Cat.No	Cat.No	Cat.No	Cat.No
4	0 577 18 <sup>(1)</sup>	1	0 577 23	2

**EXAMPLE OF SOCKETS**

ELV (p. 383)	IP 44
20/25 V~	16 A 2P 0 552 45
	32 A 2P 0 552 95
Domestic pin (p. 383)	IP 54 <sup>(3)</sup>
250 V	16 A 2P+E 0 576 72/76
LV (p. 382)	IP 44 : IP 66-67
200/250 V~	16 A 2P+E 5 551 84 : 5 553 84
	32 A 2P+E 5 552 84 : 5 554 84
	63 A 2P+E - : 5 555 84
380/415 V~	16 A 3P+E 5 551 88 : 5 553 88
	3P+N+E 5 551 89 : 5 553 89
	32 A 3P+E 5 552 88 : 5 554 88
	3P+N+E 5 552 89 : 5 554 89
	63 A 3P+E - : 5 555 88
	3P+N+E - : 5 555 89

**Examples of most common combinations with bases for 280 x 125 mm faceplates**

Base	Total number of sockets on the base	Socket combination	Face plate according to the socket intensity		
			16 A	32 A	63 A
0 577 11 or 0 577 20	2	2 x 16 A or 2 x 32 A	0 577 18	-	-
	3	2 x 16 A interlocked sw.	0 577 23	-	-
0 577 03	4	3 x 16 A	0 577 14	-	-
		4 x 16 A or 4 x 32 A	0 577 18 x 2	-	-
	5	2 x 16 or 32 A + 2 x 63 A	0 577 19 x 2	-	-
		3 x 16 or 32 A + 1 x 63 A	0 577 18 + 0 577 19	-	-
0 577 04	6	4 x 16 A interlocked sw.	0 577 23 x 2	-	-
		3 x 16 A + 1 x 16 or 32 A + 1 x 63 A	0 577 14 + 0 577 19	-	-
	7	3 x 16 A + 2 x 16 or 32 A	0 577 14 + 0 577 18	-	-
		6 x 16 A or 32 A	0 577 18 x 3	-	-
	8	3 x 16 or 32 A + 3 x 63 A	0 577 19 x 3	-	-
		5 x 16 or 32 A + 1 x 63 A	0 577 18 x 2 + 0 577 19	-	-
4 x 16 or 32 A + 2 x 63 A		0 577 18 + 0 577 19 x 2	-	-	
9	6 x 16 A interlocked sw.	0 577 23 x 3	-	-	
	3 x 16 A + 2 x 16 or 32 A + 2 x 63 A	0 577 14 + 0 577 19 x 2	-	-	
7	3 x 16 A + 4 x 16 or 32 A	0 577 14 + 0 577 18 x 2	-	-	
	3 x 16 A + 3 x 16 or 32 A + 1 x 63 A	0 577 14 + 0 577 18 + 0 577 19	-	-	
8	6 x 16 A + 1 x 16 or 32 A + 1 x 63 A	0 577 14 x 2 + 0 577 19	-	-	
	6 x 16 A + 2 x 16 or 32 A	0 577 14 x 2 + 0 577 18	-	-	
9	16 A	0 577 14 x 3	-	-	

1: Supplied with blanking plate - 2: To be fixed horizontally except 16 A domestic pin sockets, vertically (IP 44 - connected) - 3: IP 54 cover closed - IP 44 connected  
 4: External dimensions: H x W - 5: Interlocked switched socket with small flange - 6: IP 55 - Interlocked switched socket with small flange - 7: Can be used with the wall mounting lugs Cat.No 0 019 69 (p. 286)