

Hotel equipment

Arteor wiring devices round version



Support frame and plate selection charts **p. 476 to 487**

Mechanisms supplied with rocker plates, to be equipped with support frames (p. 476) and plates (p. 480 to 487)

Pack	Cat.Nos	Lighting control	Pack	Cat.Nos	Hotel bedroom call indicators
10 10	5 732 85 5 737 85	Master switch - 2 modules 2-way double pole 20 AX - 250 V~ for general control: all ON / all OFF ○ White ● Magnesium			Enable the resident to inform hotel staff of the room status Two settings are possible: - Do not disturb - Please clean the room 2 x 1 module
10 10	5 732 87 5 737 87	Master push-button - 2 modules 2-way 6 A - 250 V~ for general control: all ON/ all OFF ○ White ● Magnesium	5 5	5 720 67 5 725 67	Indicator for corridor Indicator lamp and bell push Installed in the corridor, display calls Supplied with LED ○ White ● Magnesium
5 5	5 732 95 5 737 95	Switch for bed lights - 2 x 1 module 2 x 2-way switch - 10 AX - 250 V~ ○ White ● Magnesium	5 5	5 720 74 5 725 74	Internal control unit Allows the user to select the desired setting Supplied with LED ○ White ● Magnesium
5 5	5 732 97 5 737 97	Push-button for bed lights - 2 x 1 module 2 x 2-way push-button - 6 A - 250 V~ ○ White ● Magnesium			Buzzers 230 V - 2 modules ○ White ● Magnesium
10 10	5 732 23 5 737 23	Electric roller blinds control - 250 VA Double switch 10 A - 2 modules For direct control of a motor (mechanism with fixed positions) ○ White ● Magnesium	10 10	5 722 08 5 722 48	Reading lights Fitted with maintenance-free LEDs LED colours: 3000 K (neutral white) 230 V power supply - energy class A Screw terminals For installation in the bedhead Offers directional lighting Equipped with a flexible cable so the head can swivel Built-in dimmer Consumption 3.3 W Luminous flux 110 lumen (equivalent to 15 W incandescent) Service life 4000 hours For installation in box depth 40 mm min. 2 modules
10 10	5 732 25 5 737 25	Double push-button 10 A - 2 modules For control via automatic box (N/O mechanism) ○ White ● Magnesium			Round version ○ White ● Magnesium
10 10	5 732 35 5 737 35	Curtain control - 250 VA Double switch 10 A - 2 modules For direct control of a motor (mechanism with fixed positions) ○ White ● Magnesium	1 1	5 722 56 5 727 56	
10 10	5 732 37 5 737 37	Double push-button 10 A - 2 modules For control via automatic box (N/O mechanism) ○ White ● Magnesium			

RJ 45 and audio/video sockets,
p. 468-472

