



7 645 82

7 645 88

Mechanisms supplied with cover plates and support frames in flow-pack
To be equipped with plates (p. 539)
Screw terminals
Fixing with screws or claws (supplied)

Pack	Cat.Nos	Automatic switches
1	7 645 83	IR detection Detection field: 120° Detection range: 8 m Time delay adjustable from 10 s to 10 min Light level threshold adjustable from 5 to 1275 lux 2-wire, without neutral Allow the control of: - 3 to 100 W LED and compact fluorescent lamps, - 3 to 250 VA LED, CFL, halogen and fluorescent tubes with ferromagnetic or electronic ballast, - 3 to 250 W halogen (230 V) and incandescent lamps If several sensors are installed on the same circuit, the minimum load changes: refer to the technical sheet Possibility to install up to 3 sensors in parallel Consumption on standby: 0.02 W To be used without override ○ White ● Ivory
1	7 646 83	
1	7 645 82	3-wire, with neutral Allow the control of: - 0 to 50 W LED and compact fluorescent lamps, - 0 to 200 VA LED, CFL and halogen lamps with ferromagnetic or electronic ballast, - 0 to 150 VA fluo tubes with ferromagnetic or electronic ballast - 0 to 400 W halogen (230 V) and incandescent lamps Only 1 sensor per circuit. No remote manual control with push-button Consumption on standby: 0.55 W ○ White ● Ivory
1	7 646 82	
1	7 645 88	Rotary dimmers 300 W - 2-wire Equipped with overvoltage and short-circuit protection When switched on, gradually (2 seconds) light up at the level set before last switch-off Can be remotely controlled via non-illuminated push-buttons, with each push-button able to perform the ON/OFF and dimming function Screw terminals For all types of lamps : - dimmable LEDs: 5 W to 75 W (10 lamps max.) - halogen with ferromagnetic or electronic transformer: 5 VA to 300 VA - fluorescent tube - ballast: 5 VA to 300 VA - halogen and incandescent 240 V~ : 5 W to 300 W ○ White ● Ivory
1	7 646 88	



7 645 11

Mechanisms supplied with cover plates and support frames in flow-pack
To be equipped with plates (p. 539)
Screw terminals
Fixing with screws or claws (supplied)

Pack	Cat.Nos	Shutter controls
10	7 645 11	Switches 3 positions (Raise / Stop / Lower) for direct motor control ○ White ● Ivory
10	7 646 11	
10	7 645 12	Push-buttons ○ White ● Ivory
10	7 646 12	
1	6 647 93	Keycard switches To operate the room's electrical circuits Turn off 30 seconds after the card is removed For cards of maximum 54 mm length Supplied without claws, add accessory Cat.No 6 650 99 ○ White ● Ivory
1	6 648 93	
1	7 645 87	Electronic room thermostat For direct radiant ceiling panels and underfloor heating Adjustment range: from 10 °C to 30 °C Frost protection 7 °C Adjustment precision: 0.5 °C 1 potential free N/O contact Switching capacity: 8 A - 250 V~ - resistive circuit 2 A - 250 V~ - inductive circuit Power supply: 230 V~ 50/60 Hz Adjustable brightness of LEDs Can be associated with a clock for comfort and eco mode ○ White ● Ivory
1	7 646 87	

