
















Mallia™

telephone, data, television, shaver socket and cable outlets - complete white



Polycarbonate front cover plates with a matt finish. Compact mechanism for greater wiring space
Supplied with 2 screws M 3.5 for BS boxes. Supplied complete with plate. Dim.: 86 x 86 mm

Pack	Cat.Nos	Telephone sockets	Pack	Cat.Nos	Television sockets
5	2 811 60	RJ 11 sockets - 4 contacts 1/4 turn, tool-less connector ○ White 	5	2 811 57	For DVBT and satellite installation (with individual demodulator) DVBT HDTV compatible TV: male connector (Ø9.5 mm) R: female connector (Ø9.5 mm) SAT: "F" type connector Recommended coaxial cable: 17 VATC TV-R-SAT socket TV: 5-68/120 - 862 MHz R: 87.5-108 MHz SAT: 950-2400 MHz Star low attenuation 1.5 dB ○ White 
5	2 811 63	Double RJ 11 sockets - 4 contacts 1/4 turn, tool-less connector ○ White 	5	2 811 53	TV-R socket TV: 5-68/120 - 862 MHz R: 87.5-108 MHz Star 1.5 dB ○ White 
5	2 811 68	BS master telephone sockets ○ White 	10	2 811 51	TV socket TV: 0-2400 MHz. Star low attenuation 1 dB ○ White 
5	2 811 69	BS secondary telephone sockets ○ White 	10	2 811 52	TV socket "F" type with screws SAT: 0-2400 MHz. Star attenuation 1 dB ○ White 
5	2 811 61	Data sockets RJ 45 Cat. 5e UTP ○ White 	1	2 811 35	Shaver socket Conform to BS EN 61558-2-5 230 V / 120 V~ - 50/60 Hz. Dim.: 86 x 146 mm Suitable for use with European, British and Australian 2 pin plugs ○ White 
5	2 811 62	RJ 45 Cat. 6 UTP ○ White 	5	2 811 65	Cable outlets Conform to BS 5733 20 A ○ White 
5	2 811 64	Double RJ 45 Cat. 5e UTP ○ White 	5	2 811 48	45 A ○ White 
5	2 811 65	Double RJ 45 Cat. 6 UTP ○ White 			
5	2 811 66	Telephone and data sockets RJ 11 + RJ 45 sockets Cat. 5e UTP ○ White 