



8 324 78



8 320 79



8 320 44

Sleek design

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

GG: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos	Single pole socket outlets 13 A - 250 V \sim with USB charger	Pack	Cat.Nos	Socket outlets 15 A - 250 V \sim
1	8 320 78	<p>Conform to BS 1363-2 USB charger conform to IEC 60950-1</p> <p>1 gang switched USB Type-A 2.4 A - 5 V\equiv - 12 W Consumption in passive mode < 0.08 W</p> <ul style="list-style-type: none"> ● Brushed Stainless Steel ● Polished Stainless Steel ● Glossy Gold 	1	8 320 89	<p>Conform to BS 546 Patented 3 pin safety shutter mechanism For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm</p> <p>1 gang switched</p> <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 78		1	8 322 89	
1	8 324 78		1	8 324 89	
1	8 320 79	<p>2 gang switched USB Type-A + Type-C™ 3 A - 5 V\equiv - 15 W Consumption in passive mode < 0.08 W</p> <ul style="list-style-type: none"> ● Brushed Stainless Steel ● Polished Stainless Steel ● Glossy Gold 	1	8 320 69	<p>Conform to BS 546 Patented 3 pin safety shutter mechanism For flush-mounting, back box to be min. 25 mm deep Nominal plate dimensions: 86 x 86 mm</p> <p>1 gang switched - single pole</p> <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 79		1	8 322 69	
1	8 324 79		1	8 324 69	
1	8 320 60	<p>Double pole socket outlets 13 A - 250 V\sim Conform to BS EN 1363: Part. 2 With safety shutter mechanism For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm (1 gang) 86 x 146 mm (2 gang) ASTA licence </p> <p>1 gang switched</p> <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold 	1	8 320 59	<p>Conform to BS 546 For flush-mounting, back box to be min. 25 mm deep Nominal plate dimensions: 86 x 86 mm</p> <p>1 gang unswitched</p> <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 60		1	8 322 59	
1	8 324 60		1	8 324 59	
1	8 320 61	<p>1 gang switched with blue LED power indicator</p> <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold 	1	8 320 44	<p>Double USB sockets Conform to IEC 62684 For flush-mounting, back box to be min. 40 mm deep Input voltage: 110 V/ 230 V 5 V (output) - 2400 mA. Wiring with 1.5 mm² and 2.5 mm² (only live and neutral)</p> <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold
1	8 322 61		1	8 322 44	
1	8 324 61		1	8 324 44	
1	8 320 70	<p>2 gang switched</p> <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold 	1	8 320 44	
1	8 322 70		1	8 322 44	
1	8 324 70		1	8 324 44	
1	8 320 71	<p>2 gang switched with blue LED power indicator</p> <ul style="list-style-type: none"> ● Brushed stainless steel ● Polished stainless steel ● Glossy gold 	1	8 320 44	
1	8 322 71		1	8 322 44	
1	8 324 71		1	8 324 44	