















Synergy™

British standard socket outlets, RCD sockets and fused connection units - Metalclad



Front plates: grey epoxy coated steel. Terminal screws captive and backed off ready for cabling - large angled terminal entries
 Supplied complete with close fit 43 mm deep surface-mounting back box

Pack	Cat.Nos	Socket outlets 13 A - 250 V~	Pack	Cat.Nos	RCD sockets 13 A - 250 V~ (continued)
5	7 338 65	Conform to BS 1363 - Part 2: 1995 With safety shutter mechanism Flush-mounting back box: min. 25 mm deep 1 gang - unswitched Nominal plate dimensions: 86 x 86 mm 	1	7 338 81	ELR - DP 30 mA Trips in the event of a power failure Ideal for applications where it is desirable to automatically re-activate equipment after a power failure. E.g. fridge, freezer, unmanned areas 1 gang Nominal plate dimensions: 86 x 86 mm 
5	7 338 75	2 gang - unswitched Nominal plate dimensions: 86 x 146 mm 	1	7 338 83	2 gang Nominal plate dimensions: 86 x 146 mm 
Double pole socket outlets 13 A - 250 V~					
Conform to BS 1363 - Part 2: 1995 With safety shutter mechanism Flush-mounting back box: min. 25 mm deep					
Switched					
5	7 338 60	1 gang Nominal plate dimensions: 86 x 86 mm 	5	7 338 88	1 gang - unswitched 
5	7 338 70	2 gang Nominal plate dimensions: 86 x 146 mm 	5	7 338 89	1 gang - switched 
Switched with red LED power indicator					
5	7 338 61	1 gang Nominal plate dimensions: 86 x 86 mm 			
5	7 338 71	2 gang Nominal plate dimensions: 86 x 146 mm 			
RCD sockets 13 A - 250 V~					
Conform to BS 7288: 1990 and BS 1363 - Part 2: 1995 Conventional earth pin release shutter Maximum operating current 16 A Electronic RCD module with a membrane switch for "test and reset" Flush mounting back box : min. 25 mm deep					
ELO - DP 30 mA					
Trips in the event of a power failure Ideal for applications where it is desirable to prevent automatic reactivation of equipment after a power failure. For hazardous, e.g. machinery, power tools					
1	7 338 80	1 gang Nominal plate dimensions: 86 x 86 mm 	5	7 338 34	Double pole switched Without cord outlet 
1	7 338 82	2 gang Nominal plate dimensions: 86 x 146 mm 	5	7 338 35	With red LED power indicator 
Fused connection units 13 A - 250 V~					
Conform to BS 1363 - Part 4: 1995. Fused 13 A (fuse supplied). Fuse drawer retained by quarter turn catch, drawer padlockable in open position for safety. Flush-mounting back box: min. 25 mm deep Nominal plate dimensions: 86 x 86 mm					
Double pole switched					
Without cord outlet					
With red LED power indicator					
With cord outlet					
With cord outlet + red LED power indicator					
Unswitched					
Without cord outlet					
With red LED power indicator					
With cord outlet					
With cord outlet + red LED power indicator					