










Connectivity and housing selection tables

configure your system (continued)

LCS ³ 19" SERVER ENCLOSURES (WITHOUT SIDE PANELS) (p. 758)			Depth 1000 mm	Depth 1100 mm	Depth 1200 mm
	42 U	Width 600 mm	4 460 00	4 460 01	4 460 02
	42 U	Width 800 mm	4 460 03	4 460 04	4 460 05
	46 U	Width 600 mm	4 460 06	4 460 07	4 460 08
	46 U	Width 800 mm	4 460 09	4 460 10	4 460 11
LCS ³ 19" SERVER ENCLOSURES (WITHOUT SIDE PANELS) - WITH AIRFLOW MANAGEMENT (p. 758)					
	42 U	Width 600 mm	4 460 12	4 460 13	4 460 14
	42 U	Width 800 mm	4 460 15	4 460 16	4 460 17
	46 U	Width 600 mm	4 460 18	4 460 19	4 460 20
	46 U	Width 800 mm	4 460 21	4 460 22	4 460 23
LCS ³ 19" SIDE PANELS - SET OF 2 INCLUDED PLINTHS (p. 758)					
	42 U	-	4 460 24	4 460 25	4 460 26
	46 U	-	4 460 27	4 460 28	4 460 29
LCS ³ 19" SERVER ENCLOSURES - FLAT PACK (WITH SIDE PANELS) (p. 758)					
	42 U	Width 600 mm	4 460 30	4 460 31	4 460 32
	42 U	Width 800 mm	4 460 33	4 460 34	4 460 35
	46 U	Width 600 mm	4 460 36	4 460 37	4 460 38
	46 U	Width 800 mm	4 460 39	4 460 40	4 460 41
LCS ³ 19" CABLING CABINETS (p. 764)			Depth 800 mm	Depth 1000 mm	
	25 U	Width 800 mm	4 460 80	4 460 81	-
	37 U	Width 800 mm	4 460 82	4 460 83	-
	41 U	Width 800 mm	4 460 84	4 460 85	-
	46 U	Width 800 mm	4 460 86	4 460 87	-
LCS ³ 19" WALL MOUNTED ENCLOSURES (p. 764)			Depth 525 mm	Depth 625 mm	
	6 U	Width 600 mm	4 461 80	-	-
	9 U	Width 600 mm	4 461 81	4 461 82	-
	12 U	Width 600 mm	4 461 83	4 461 84	-
	15 U	Width 600 mm	4 461 85	4 461 86	-
	21 U	Width 600 mm	-	4 461 87	-
LCS ³ ZERO-U SINGLE PHASE VERTICAL PDU - POWER DISTRIBUTION UNITS (p. 769)			Connection on 6 mm ² terminal block	3m cord on 32 A 2P+E plug	With Ammeter
	24 outlets	German Standard	6 468 52	6 468 53	-
	24 outlets	British Standard	-	6 468 54	-
	24 outlets	French Standard	6 468 50	6 468 51	-
	24 outlets	Italian standard 	-	6 468 59	-
	24 outlets	C13 - IEC 60320 standard	6 468 56	6 468 57	-
	24 outlets	C13 (20) and C19 (4) - IEC 60320 standard	6 468 60	6 468 61	6 468 65
LCS ³ ZERO-U 3 PHASES VERTICAL PDU - POWER DISTRIBUTION UNITS (p. 770)			Connection on 6 mm ² terminal block	3m cord on 16 A 3P+N+E plug	With Ammeter
	24 outlets	C13 (18) and C19 (6) - IEC 60320 standard	-	6 468 70	6 468 75