

Floor boxes for tiles/marble

Steel & polycarbonate floor box for South Africa



6 896 56 + 0 896 04



6 896 51 + 0 896 04



6 896 56 equipped with Arteor mechanisms



6 896 51 equipped with Arteor mechanisms

Technical characteristics **see e-catalogue**

Conforms to IEC/EN 60670-23
Compatible with screed floor system

Pack	Cat.Nos	Lid and trim for tiles/marble
1	6 896 56	Single cable outlet stainless steel lid and trim Edge trim for tile 8 to 15 mm thickness
1	6 896 55	Single cable outlet powder coated lid and trim Edge trim for tile 8 to 15 mm thickness Grey RAL 7031
1	6 896 51	Double cable outlet stainless steel lid and trim Edge trim for tile 8 to 15 mm thickness
1	6 896 52	Double cable outlet stainless steel lid and trim Edge trim for tile 15 to 22 mm thickness
1	0 896 04	Specific backbox for lids and trims for tiles/marble For installation of floor boxes Cat.Nos 6 896 22/23/51/52/55/56 for screed floor system



CFB3EC

Pack	Cat.Nos
1	CFB3EC
1	CFB6MOD
1	CFBBLANK

3-compartment floor box for South Africa

Floor box

Recommended hole cut out size: 305 x 225 mm
Standard depth: 75 mm
Universal knockouts (20/25 mm) to each compartment
Manufactured from pre-galvanised steel and polycarbonate/ABS
Supplied with back box



Support plate for Arteor mechanism
For 6 modules

Blank plate
For unused space