












## Choix de la répartition VX<sup>3</sup> optimisée

Répartition VX <sup>3</sup>	Imax (A)	Montage	XL <sup>3</sup> 4000				
			position des barres	alignées		étagées	
<b>Jeux de barres VX<sup>3</sup></b> 	<b>1600 A</b> (p. 404)	Barre 630 A : 0 373 54 Barre 800 A : 0 373 55 Barre 1000 A : 0 373 56 Barre 1250 A : 0 373 57 Barre 1600 A : 0 373 58	position des barres	alignées		étagées	
			entraxe des barres	75 mm	125 mm	75 mm	125 mm
			support fixe	0 373 66/86	0 373 68	0 373 67	0 373 69
			support volant	0 373 50	0 373 51	-	-
		 vertical en fond d'armoire	L : 475 mm	●			
			L : 725 mm	●	●		
			L : 975 mm	●	●		
		 vertical latéral en armoire derrière montants	P : 475 mm				
			P : 725 mm	● <sup>(1)</sup>	●		
			P : 975 mm	● <sup>(1)</sup>	●		
		 vertical en gaine à câbles	P : 475 mm	● <sup>(1)</sup>		●	
			P : 725 mm	● <sup>(1)</sup>	●	●	●
			P : 975 mm	● <sup>(1)(2)</sup>	● <sup>(2)</sup>	● <sup>(2)</sup>	● <sup>(2)</sup>
		 horizontal haut ou bas	P : 475 mm	● <sup>(1)</sup>			
			P : 725 mm	● <sup>(1)</sup>	●		
			P : 975 mm	● <sup>(1)</sup>	●		
		 transfert horizontal	P : 475 mm				
			P : 725 mm	● <sup>(1)</sup>	●		
			P : 975 mm	● <sup>(1)</sup>	●		
		Répartition VX <sup>3</sup>	Imax (A)	Montage	réf.	XL <sup>3</sup> 400	XL <sup>3</sup> 800
	<b>800 A</b> (p. 406)	 vertical en fond d'armoire	Support : 4 044 60 Support talon : 4 044 61 Barre 800 A : 4 044 33		●	●	
		 vertical en gaine à câble	Support : 4 044 70 Support talon : 4 044 71 Barre 800 A : 4 044 33			●	
	<b>400 A</b> (p. 406)	 vertical en fond d'armoire	Fond isolant : <b>4 044 36</b> Support : <b>4 044 37</b> Support talon : <b>4 044 38</b> Barre 250 A : <b>4 044 30</b> Barre 400 A : <b>4 044 31</b>	●			
		 vertical en gaine à câble	Support : <b>4 044 50</b> Support talon : <b>4 044 51</b> Barre 250 A : <b>4 044 30</b> Barre 400 A : <b>4 044 31</b>	●			

1 : Seules ces configurations acceptent les kits de raccords préfabriqués VX<sup>3</sup> optimisé  
 2 : Avec montant réf. 0 205 20/51