

Tableau de choix des équipements et des enveloppes

configurez votre système LCS³ et LCS² (suite)

CORDONS DE BRASSAGE ET UTILISATEURS RJ 45 (p. 1014)				LCS ³					
				LCS ³ cat. 8	LCS ² cat. 6 _A	LCS ² cat. 6			
	S/FTP	Impédance 100 Ω	0,5 m	-	● 0 518 16	-			
			1 m	-	● 0 517 80	● 0 517 52			
			2 m	-	● 0 517 81	● 0 517 53			
			3 m	-	● 0 517 82	● 0 517 54			
			5 m	-	● 0 517 83	● 0 517 55			
	PVC F/UTP	Impédance 100 Ω	0,5 m	-	-	● 0 518 15			
			1 m	-	-	● 0 517 62			
			2 m	-	-	● 0 517 63			
			3 m	-	-	● 0 517 64			
			5 m	-	-	● 0 517 65			
	U/UTP	Impédance 100 Ω	0,5 m	-	-	● 0 518 18			
			1 m	-	-	● 0 517 72			
			2 m	-	-	● 0 517 73			
			3 m	-	-	● 0 517 74			
			5 m	-	-	● 0 517 75			
CABLES CUIVRE (TOURETS DE 305 OU 500 M) (p. 1012, 1014, 1017)									
	S/FTP	4 paires	500 m	0 337 88	● 0 327 77	-			
	SF/UTP	4 paires	500 m	-	-	● 0 327 57			
	F/UTP	4 paires	305 m	-	-	● 0 328 56			
			500 m	0 337 86	● 0 327 78	● 0 327 56			
	F/FTP	4 paires	2 x 4 paires	500 m	-	● 0 328 78	● 0 327 76		
			2 x 4 paires	500 m	-	● 0 327 99	-		
				500 m	-	● 0 327 98	-		
CORDONS DE BRASSAGE FIBRE OPTIQUE LCS³ (p. 1036)					OS 2 (UPC) monomode 9/125 μm	OM 4 multimodes 50/125 μm	OM 3 multimodes 50/125 μm		
	Cordons duplex SC/SC		1 m	0 326 00	0 326 30	0 326 09			
			2 m	0 326 01	0 326 31	0 326 10			
			3 m	0 326 02	0 326 32	0 326 11			
	Cordons duplex SC/LC		1 m	0 326 03	-	0 326 12			
			2 m	0 326 04	-	0 326 13			
			3 m	0 326 05	-	0 326 14			
	Cordons duplex LC/LC		0,5 m	0 326 28	0 326 33	-			
			1 m	0 326 06	0 326 34	0 326 15			
			2 m	0 326 07	0 326 35	0 326 16			
			3 m	0 326 08	0 326 36	0 326 17			
			5 m	0 326 29	0 326 37	-			
	Cordons duplex Uniboost LC/LC polarité réversible		1 m	0 326 86	0 326 95	-			
			2 m	0 326 87	0 326 96	-			
			3 m	0 326 88	0 326 97	-			
			5 m	0 326 89	0 326 98	-			
			10 m	0 326 92	0 326 99	-			
CABLES OPTIQUES (TOURET) LCS³ (p. 1035)									
	Intérieur/extérieur		4 fibres	Libres	0 325 02	0 325 43	0 325 37		
			8 fibres	Libres	0 325 03	0 325 44	0 325 38		
			6 fibres	Libres	0 325 12	-	-		
				Serrées	-	0 326 65/66	0 325 10		
			12 fibres	Libres	0 325 14	0 325 45	0 325 39		
				Serrées	0 325 50	0 326 67	0 325 11		
			24 fibres	Libres	0 325 51	-	0 325 53		
				Serrées	-	0 326 68	0 325 52		
			Extérieur, armé acier anti-rongeurs, libres		4 fibres		0 325 23	0 325 46	-
					8 fibres		0 325 24	0 325 47	0 325 40
					6 fibres libres		0 325 13	-	-
					12 fibres		0 325 15	0 325 48	0 325 41
24 fibres		0 325 25			-	0 325 42			