



Ref. Certif. No.

FR 692820B

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST
CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

SYSTEME CEI D'ACCEPTATION MUTUELLE DE
CERTIFICATS D'ESSAIS DES EQUIPEMENTS
ELECTRIQUES (IECEE) METHODE OC

CB TEST CERTIFICATE / CERTIFICAT D'ESSAI OC

Product
Produit

Fixed socket-outlet

Name and address of the applicant
Nom et adresse du demandeur

LEGRAND FRANCE

128, avenue du Maréchal de Lattre de Tassigny, B.P. 523 - 87045 LIMOGES
CEDEX - France

Name and address of the manufacturer
Nom et adresse du fabricant

LEGRAND FRANCE

128, avenue du Maréchal de Lattre de Tassigny B.P. 523 - 87045 LIMOGES
CEDEX - France

Name and address of the factory
Nom et adresse de l'usine

See annex 1

Note : When more than one factory, please report on page 2
Note : Lorsqu'il y a plus d'une usine, veuillez utiliser la 2ème page

Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

16 A, 250 V~

Trademark (if any)
Marque de fabrique (si elle existe)



Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeur

/

Model / Type Ref.
Ref. De type

Series MOSAIC
References: see annex

Additional information (if necessary may also be
reported on page 2)
Informations complémentaires (si nécessaire, peuvent
être indiquées sur la 2ème page)

Supersedes CBTC FR 683664B date on 2016-06-08:
Addition of references and accessories

A sample of the product was tested and found
to be in conformity with
Un échantillon de ce produit a été essayé et a été
considéré conforme à la

PUBLICATION **EDITION**
IEC 60884-1:2002(ed.3) +A1:2006 +A2:2013

As shown in the Test Report Ref. No. which forms part
of this Certificate
Comme indiqué dans le Rapport d'essais numéro de
référence qui constitue partie de ce Certificat

144476-692829 and see annex

This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**



Laboratoire Central des Industries Électriques

33, av du Général Leclerc - BP 8
FR 92266 Fontenay-aux-Roses cedex
www.lcie.fr



Date:

2016-12-19

Signature:

Jean-François BRUEL
Certification Officer

Annex 1 : List of Manufacturers and Factories

Fixed socket-outlet

Factory	Manufacturer
LEGRAND FRANCE 128, avenue du Maréchal de Lattre de Tassigny B.P. 523 - 87045 LIMOGES CEDEX - France	LEGRAND FRANCE 128, avenue du Maréchal de Lattre de Tassigny B.P. 523 - 87045 LIMOGES CEDEX - France
LEGRAND FRANCE ISERE Avenue de Romans B.P. 95 - 38163 SAINT MARCELLIN CEDEX - France	LEGRAND FRANCE 128, avenue du Maréchal de Lattre de Tassigny B.P. 523 - 87045 LIMOGES CEDEX - France
LEGRAND FRANCE Route d'Evron BP 36 - 72140 SILLE LE GUILLAUME - France	LEGRAND FRANCE 128, avenue du Maréchal de Lattre de Tassigny B.P. 523 - 87045 LIMOGES CEDEX - France
LEGRAND MAGYARORSZAG VILLAMOSSAGI RENDSZEREK ZRT Ipartelep ut 14 pf 10 - 6600 SZENTES - Hungary	LEGRAND FRANCE 128, avenue du Maréchal de Lattre de Tassigny B.P. 523 - 87045 LIMOGES CEDEX - France
NIEF PLASTIC HUNGARIA Iparis Park 07/6 - 5440 KUNSZENMARTON - Hungary	LEGRAND FRANCE 128, avenue du Maréchal de Lattre de Tassigny B.P. 523 - 87045 LIMOGES CEDEX - France
PLASTIVALOIRE ZI Nord - LANGEAIS 37130 - France	LEGRAND FRANCE 128, avenue du Maréchal de Lattre de Tassigny B.P. 523 - 87045 LIMOGES CEDEX - France

Additional Information (if necessary)
Informations complémentaires (si nécessaire)



Laboratoire Central des Industries Électriques
33,av du Général Leclerc – BP 8
FR 92266 Fontenay-aux-Roses cedex
www.lcie.fr

Date:

2016-12-19

Signature:

Jean-François BRUEL
Certification Officer



Relevant documents :

Test reports n° 80640-569801/A1, 60021487-514363A/A1, 60032294-530935-CR, 60051320-552098/A1, 60051320-552296A/A1, 60051549-552343A/A1, 60052084-553026/A1, 109475-618400A, 112252-623334A, 118896-637230A1, 127649-655969, 130899-663536Cr2016-10-05, 136736-675846A, 140943-683663, 140943-683665A.

REFERENCES – MAIN CHARACTERISTICS**Mechanisms**

Type reference	References	Number of sockets	Terminals	Colour of cover	Specificity
PFA1	0 771 11	2P+E	slt	white or black or grey	
	0 995 94	2P+E	slt	white	
	0 996 95	2P+E	slt	white	
	0 996 80	2P+E	slt	white	
	0 771 99	2P+E	slt	white	
	0 771 40	2P+E	slt	white	for Czech Republic
	0 771 12	2P+E	slt	white antibacterial or grey	with pilot light
	0 787 01	2P+E	slt	white antibacterial	
	0 771 16	2P+E	slt	green antibacterial	
	0 771 46	2P+E	slt	green antibacterial	for Czech Republic
	0 771 17	2P+E	slt	orange antibacterial	
	0 771 47	2P+E	slt	orange antibacterial	for Czech Republic
	0 771 18	2P+E	slt	red antibacterial	
	0 771 26	2P+E	slt	red antibacterial	with pilot light
	0 771 41	2P+E	slt	red antibacterial	for Czech Republic
	0 771 19	2P+E	slt	white	with lid
	0 771 49	2P+E	slt	white	for Czech Republic with lid
	0 791 21	2P+E	slt	anthracite	
	0 792 71	2P+E	slt	aluminium	
	0 792 14	2P+E	slt	aluminium	for Czech Republic
	0 771 32	2P+E	slt	white antibacterial	mobile face of entry plug
	0 996 24	2P+E	slt	white antibacterial	mobile face of entry plug
	0 791 32	2P+E	slt	anthracite	mobile face of entry plug
	0 771 33	2P+E	slt	red antibacterial	mobile face of entry plug
	0 771 35	2P+E	slt	white antibacterial	with pilot light mobile face of entry plug
	0 787 04	2P+E	slt	green antibacterial	mobile face of entry plug
	0 921 10	2P+E	slt	Inox	
	0 921 11	2P+E	slt	Inox	
PFA2	0 771 10	2P	slt	white	
	0 996 41	2P	slt	white	
	0 996 94	2P	slt	white	
PFA3	0 771 45	2P+E	slt	white	angle of 45°
	0 771 48	2P+E	slt	white	with pilot light, angle of 45°



Type reference	References	Number of sockets	Terminals	Colour of cover	Specificity
PFAD1	0 771 34	2 x 2P+E	slt	white	mobile face of entry plug
	0 791 34	2 x 2P+E	slt	Anthracite	mobile face of entry plug
	0 793 44	2 x 2P+E	slt	Aluminium	mobile face of entry plug
PFAT1	0 771 36	3 x 2P+E	slt	white	mobile face of entry plug
	0 791 36	3 x 2P+E	slt	Anthracite	mobile face of entry plug
	0 793 46	3 x 2P+E	slt	Aluminium	mobile face of entry plug
	0 771 13	2P+E	st	white	
	0 996 40	2P+E	st	white	
	0 771 14	2P+E	st	red or grey / red	tamperproof
	0 771 15	2P+E	st	red antibacterial	tamperproof with pilot light
E11	0 771 42	2 x 2P+T	slt	white	for trunking angle of 45°
	0 996 42	2 x 2P+T	slt	white	for trunking angle of 45°
	200 020	2 x 2P+T	slt	white	for trunking angle of 45°
	200 021	2 x 2P+T	slt	white	for trunking angle of 45°
	0 771 62	2 x 2P+T	slt	green	for trunking angle of 45°
	0 791 92	2 x 2P+T	slt	Anthracite	for trunking angle of 45°
	0 792 72	2 x 2P+T	slt	aluminium	for trunking angle of 45°
	0 771 72	2 x 2P+T	slt	red	for trunking angle of 45°
	0 771 64	2 x 2P+T	slt	white	for trunking angle of 45° grey push terminal
	0 792 76	2 x 2P+T	slt	aluminium	for trunking angle of 45° grey push terminal
	0 771 68	2 x 2P+T	slt	red	for trunking angle of 45° grey push terminal
	0 771 43	3 x 2P+T	slt	white	for trunking angle of 45°
	0 996 43	3 x 2P+T	slt	white	for trunking angle of 45°
	0 771 63	3 x 2P+T	slt	green	for trunking angle of 45°
	0 791 63	3 x 2P+T	slt	Anthracite	for trunking angle of 45°
	0 792 73	3 x 2P+T	slt	aluminium	for trunking angle of 45°
	0 771 73	3 x 2P+T	slt	red	for trunking angle of 45°
	0 771 65	3 x 2P+T	slt	white	for trunking angle of 45° grey push terminal
	0 771 69	3 x 2P+T	slt	red	for trunking angle of 45° grey push terminal
	0 771 44	4 x 2P+T	slt	white	for trunking angle of 45°
	0 996 31	4 x 2P+T	slt	white	for trunking angle of 45°
	200 022	4 x 2P+T	slt	white	for trunking angle of 45°
	200 023	4 x 2P+T	slt	white	for trunking angle of 45°
	0 771 74	4 x 2P+T	slt	red	tamperproof for trunking angle of 45°
	0 771 52	2 x 2P+T	slt	red	tamperproof for trunking angle of 45°
	0 771 66	2 x 2P+T	slt	red	tamperproof for trunking angle of 45° grey push terminal
	0 771 53	3 x 2P+T	slt	red	tamperproof for trunking angle of 45°
	0 771 67	3 x 2P+T	slt	red	tamperproof for trunking angle of 45° grey push terminal
	0 771 54	4 x 2P+T	slt	red	tamperproof for trunking angle of 45°



Type reference	References	Number of sockets	Terminals	Colour of cover	Specificity
E10	0 771 01	2P+T	slt	white	for trunking with soluclip
	0 771 02	2 x 2P+T	slt	white	for trunking with soluclip
	0 771 82	2 x 2P+T	slt	black	for trunking with soluclip
	0 771 92	2 x 2P+T	slt	green	for trunking with soluclip
	0 771 03	3 x 2P+T	slt	white	for trunking with soluclip
	0 771 83	3 x 2P+T	slt	black	for trunking with soluclip
	0 771 04	4 x 2P+T	slt	white	for trunking with soluclip
	0 771 21	2P+T	slt	red	tamperproof for trunking with soluclip
	0 771 22	2 x 2P+T	slt	red	tamperproof for trunking with soluclip
	0 771 23	3 x 2P+T	slt	red	tamperproof for trunking with soluclip
	0 771 24	4 x 2P+T	slt	red	tamperproof for trunking with soluclip
	0 773 31	2P+T	slt	white	for trunking
	0 773 81	2P+T	slt	white	for trunking with frame cv 65
	0 773 32	2 x 2P+T	slt	white	for trunking
	0 773 82	2 x 2P+T	slt	white	for trunking with frame cv 65
	0 773 33	3 x 2P+T	slt	white	for trunking
	0 773 83	3 x 2P+T	slt	white	for trunking with frame cv 65
	0 773 34	4 x 2P+T	slt	white	for trunking
	0 773 84	4 x 2P+T	slt	white	for trunking with frame cv 65
	0 773 41	2P+T	slt	red	tamperproof for trunking
	0 773 91	2P+T	slt	red	tamperproof for trunking with frame cv 65
	0 773 42	2 x 2P+T	slt	red	tamperproof for trunking
	0 773 92	2 x 2P+T	slt	red	tamperproof for trunking with frame cv 65
	0 773 43	3 x 2P+T	slt	red	tamperproof for trunking
	0 773 93	3 x 2P+T	slt	red	tamperproof for trunking with frame cv 65
	0 773 44	4 x 2P+T	slt	red	tamperproof for trunking
	0 773 94	4 x 2P+T	slt	red	tamperproof for trunking with frame cv 65
	0 773 01	2P+T	slt	white	for trunking
	0 773 51	2P+T	slt	white	for trunking with frame cv 65
	0 773 02	2 x 2P+T	slt	white	for trunking
	0 773 52	2 x 2P+T	slt	white	for trunking with frame cv 65
	0 792 22	2 x 2P+T	slt	aluminium	for trunking
	0 773 03	3 x 2P+T	slt	white	for trunking
	0 773 53	3 x 2P+T	slt	white	for trunking with frame cv 65
	0 792 23	3 x 2P+T	slt	aluminium	for trunking
	0 773 04	4 x 2P+T	slt	white	for trunking
	0 773 54	4 x 2P+T	slt	white	for trunking with frame cv 65



	References	Number of sockets	Terminals	Colour of cover	Specificity
E10	0 773 21	2P+T	slt	red	tamperproof for trunking
	0 773 71	2P+T	slt	red	tamperproof for trunking with frame cv 65
	0 773 22	2 x 2P+T	slt	red	tamperproof for trunking
	0 773 72	2 x 2P+T	slt	red	tamperproof for trunking with frame cv 65
	0 773 23	3 x 2P+T	slt	red	tamperproof for trunking
	0 773 73	3 x 2P+T	slt	red	tamperproof for trunking with frame cv 65
	0 773 24	4 x 2P+T	slt	red	tamperproof for trunking
	0 773 74	4 x 2P+T	slt	red	tamperproof for trunking with frame cv 65
	0 773 12	2 x 2P+T	slt	red	for trunking
	0 773 62	2 x 2P+T	slt	red	for trunking with frame cv 85
	0 773 13	3 x 2P+T	slt	red	for trunking
	0 773 63	3 x 2P+T	slt	red	for trunking with frame cv 85

st : screw terminals

slt : screwless terminals

Characteristics

standard sheet	I NF C 61-314 / V (CEE 7) - IIIA NF C 61-314 / I (CEE 7)
Rated current (A)	16 A
Rated voltage (V)	250 V~
Degree of protection	IP20 IP44 with cover plate 0 788 80 or plates 0 897--
Provision of earthing	with or without earthing contact
Method of connecting the cable	rewirable
Type of terminals	screw type or screwless type (rigid and flexible)
Degree of protection against electric shock	normal protection
existence of shutters	with shutters
Method of mounting	surface type or flush-type floor-type with plates 0 897--
Method of installation	design A design B with plates 0 897--



ACCESSORIES

Blank

References	Number of modules	Colour
0 770 70	1	white
0 792 70	1	aluminium
0 787 20	1	white antibacterial
0 770 71	2	white
0 791 81	2	Anthracite
0 792 80	2	aluminium
0 787 21	2	white antibacterial
4 129 52	2	grey

Pilot light

References	Voltage	Specificity
0 676 63	230V	Indicator green
0 676 64	230V	Indicator white

Frames

Between axes 71mm with screw

References	Number of gang or modules	Specificity
0 802 51	1 gang	
0 802 09	1 gang	sold by 100
0 802 60	1 gang	for illumination under frame
0 802 62	1 gang	for indicator under frame
0 802 59	3 modules	
0 802 52	2 gangs	
0 802 58	2 gangs	horizontal for illumination under frame
0 802 57	2 gangs	vertical for illumination under frame
0 802 53	3 gangs	
0 802 54	4 gangs	
0 802 64	2 x 2 gangs	
0 802 66	2 x 3 gangs	
0 802 68	2 x 10 modules	



Between axes 71mm with claws

References	Number of gang	Specificity
0 802 61	1 gang	
0 802 69	1 gang	long claws

Between axes Italy

References	Number of gang or modules	Specificity
0 802 13	3 modules	
0 802 14	4 modules	
0 802 16	6 modules	
0 802 93	3 modules CHILI	

Support DLP

References	Number of gang or modules	Specificity
0 109 21	2 modules	cv 65
0 109 41	4 modules	
0 109 61	6 modules	
0 109 81	8 modules	
0 109 22	2 modules	cv 85
0 109 42	4 modules	
0 109 62	6 modules	
0 109 82	8 modules	

Blanks

References	Number of gang	Colour
0 791 04	2 gangs	
0 791 06	3 gangs	
0 791 10	4 gangs	

Thin walls

References	Number of modules	Colour
0 802 91	2 modules	white
0 802 95	2 modules	aluminium

Modulars

References	Number of modules	Colour	Specificity
0 788 40	2 modules	white	cover for modular
0 801 29	2 modules	white	DIN rail for modular
0 802 99	2 modules	white	modular support
4 129 50	2 modules	white	modular support

Kit box + frame + plate

Export references	France references	Number of gang or modules	Colour
0 788 72	0 788 72	2 x 4 modules	white
0 788 73	0 788 73	3 x 4 modules	white
0 788 74	0 788 74	4 x 4 modules	white
0 790 72		2 x 4 modules	aluminium
0 790 73		3 x 4 modules	aluminium
0 790 74		4 x 4 modules	aluminium



Kit surface box + frame + plate

Export references	France references	Number of modules	Colour
0 788 82	0 788 86	2 x 4 modules	white
0 788 83	0 788 87	3 x 4 modules	white
0 788 84	0 788 88	4 x 4 modules	white
0 790 82		2 x 4 modules	aluminium
0 790 83		3 x 4 modules	aluminium
0 790 84		4 x 4 modules	aluminium

Boxes for surface mounting

References	Number of gang or modules	Specificity
0 802 80	1 gang	Depth 30mm
0 802 81	1 gang	Depth 40mm
0 802 82	2 gangs	vertical
0 802 83	3 gangs	vertical
0 802 84	4 gangs	
0 802 85	2 gangs	horizontal
0 802 86	3 gangs	horizontal
0 802 89	3 modules	
0 802 74	2 x 2 gangs	
0 802 76	2 x 3 gangs	
0 802 78	2 x 10 modules	

Plates for floor recessed type

References	Désignation
0 897 00	Square plate to be equipped, 1 gang inox - IP44 IK08
0 897 01	Round plate to be equipped, 1 gang inox - IP44 IK08
0 897 10	Square plate to be equipped, 1 gang bronze - IP44 IK08
0 897 11	Round plate to be equipped, 1 gang bronze - IP44 IK08
0 897 02	Rectangle plate to be equipped, 2 gang inox - IP44 IK08
0 897 12	Rectangle plate to be equipped, 2 gang bronze - IP44 IK08



Cover plates Between axes 71mm

References	Number of gang or modules	Colour	Specificity	Frame
0 788 02	1 gang 2 modules	white	sold by 100	0 802 51, 0 802 60, 0 802 61, 0 802 62, 0 802 69
0 788 99		white		
0 790 02		aluminium Z		
0 787 22		white antibacterial		
0 793 02		aluminium		
0 790 42		Anthracite		
0 788 03	3 modules	white		0 802 59
0 790 03		aluminium Z		
0 793 03		aluminium		
0 788 04	2 x 2 modules	white	horizontal	0 802 52, 0 802 58
0 790 04		aluminium Z		
0 787 25		white antibacterial		
0 793 04		aluminium		
0 790 44		Anthracite		
0 788 22	2 x 2 modules	white	vertical	0 802 52, 0 802 57
0 790 22		aluminium Z		
0 787 23		white antibacterial		
0 793 22		aluminium		
0 790 62		Anthracite		
0 788 14	4 modules	white	horizontal	0 802 52, 0 802 58
0 790 14		aluminium Z		
0 787 24		white antibacterial		
0 793 14		aluminium		
0 790 54		Anthracite		
0 788 25	5 modules	white	vertical	0 802 52, 0 802 57
0 790 25		aluminium Z		
0 793 25		aluminium		
0 788 15	5 modules	white	horizontal	0 802 52, 0 802 58
0 790 15		aluminium Z		
0 793 15		aluminium		
0 788 06	3 x 2 modules	white	horizontal	0 802 53
0 790 06		aluminium Z		
0 793 06		aluminium		
0 790 46		Anthracite		
0 788 23	3 x 2 modules	white	vertical	0 802 53
0 790 23		aluminium Z		
0 793 23		aluminium		
0 788 16	6 modules	white		0 802 53
0 790 16		aluminium Z		
0 787 26		white antibacterial		



References	Number of gang or modules	Colour	Specificity	Frame
0 793 16	8 modules	aluminium		0 802 53
0 790 56		Anthracite		
0 788 18		white		
0 790 18		aluminium Z		
0 793 18		aluminium		
0 790 58	2 x 2 x 2 modules	Anthracite		0 802 64
0 788 38		white		
0 790 38		aluminium Z		
0 793 38	2 x 5 modules	aluminium		0 802 64
0 788 30		white		
0 790 30		aluminium Z		
0 793 30	2 x 3 x 2 modules	aluminium		0 802 66
0 788 32		white		
0 790 32		aluminium Z		
0 793 32	2 x 6 modules	aluminium		0 802 66
0 788 36		white		
0 790 36		aluminium Z		
0 793 36		aluminium		
0 790 76	2 x 8 modules	Anthracite		0 802 66
0 788 37		white		
0 790 37		aluminium Z		
0 793 37		aluminium		
0 790 77	4 x 2 modules	Anthracite	horizontal	0 802 54
0 788 08		white		
0 790 08		aluminium Z		
0 793 08	10 modules	aluminium		0 802 54
0 788 10		white		
0 790 10		aluminium Z		
0 793 10	2 x 10 modules	aluminium		0 802 68
0 788 28		white		
0 790 28		aluminium Z		
0 793 28		aluminium		

Between axes 57mm

References	Number of modules	Colour	Specificity	Frame
0 788 54	2 x 2 modules	white	vertical	0 802 51, 0 802 61
0 793 54		aluminium		
0 788 64	2 x 2 modules	white	horizontal	0 802 51, 0 802 61, 0 802 14
0 793 64		aluminium		
0 788 56	3 x 2 modules	white	vertical	0 802 51, 0 802 61
0 788 66	3 x 2 modules	white	horizontal	0 802 51, 0 802 61, 0 802 16

Between axes Italy

References	Number of modules	Colour	Specificity	Frame
0 788 91	1 module	white		0 802 13, 0 802 93
0 788 92	2 modules	white	centred	0 802 13, 0 802 94
0 788 93	3 modules	white	vertical	0 802 13, 0 802 95
0 788 94	2 modules	white	separated	0 802 13, 0 802 96
0 788 90		white	blank	0 802 13, 0 802 97

IP44

References	Number of modules	Colour	Specificity	Frame
0 788 80	2 modules	white antibacterial	IP44	0 802 51, 0 802 61

