



ZODZ2.E212478 Positioning Devices - Component

Page Bottom

Positioning Devices - Component

See General Information for Positioning Devices - Component

LEGRAND FRANCE
RUE PAUL-NOUEL
76770 MALAUNAY, FRANCE

E212478

Nonmetallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Min. Install. Temp., °C(°F)	Resistant to UV Light	Flame Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max		Min	Max				
032012	1	1.6 (0.06)	18 (0.71)	80 (18)	-40 (-40)	105 (221)	0 (32)	-	-	-
032012	11	1.6 (0.06)	18 (0.71)	80 (18)	-40 (-40)	105 (221)	0 (32)	-	V-2	-
032013	11	1.6 (0.06)	33 (1.30)	80 (18)	-40 (-40)	105 (221)	0 (32)	-	V-2	-
032013	1	1.6 (0.06)	33 (1.30)	80 (18)	-40 (-40)	105 (221)	0 (32)	-	-	-
032014	1	1.6 (0.06)	46 (1.81)	80 (18)	-40 (-40)	105 (221)	0 (32)	-	-	-
032014	11	1.6 (0.06)	46 (1.81)	80 (18)	-40 (-40)	105 (221)	0 (32)	-	V-2	-
032015	11	1.6 (0.06)	33 (1.30)	130 (29)	-40 (-40)	105 (221)	0 (32)	-	V-2	-
032015	1	1.6 (0.06)	33 (1.30)	130 (29)	-40 (-40)	105 (221)	0 (32)	-	-	-
032018	1	1.6 (0.06)	46 (1.81)	130 (29)	-40 (-40)	105 (221)	0 (32)	-	-	-
032018	11	1.6 (0.06)	46 (1.81)	130 (29)	-40 (-40)	105 (221)	0 (32)	-	V-2	-
032019	11	1.6 (0.06)	77 (3.03)	130 (29)	-40 (-40)	105 (221)	0 (32)	-	V-2	-
032019	1	1.6 (0.06)	77 (3.03)	130 (29)	-40 (-40)	105 (221)	0 (32)	-	-	-
032020	1	1.6 (0.06)	102 (4.02)	130 (29)	-40 (-40)	105 (221)	0 (32)	-	-	-
032020	11	1.6 (0.06)	102 (4.02)	130 (29)	-40 (-40)	105 (221)	0 (32)	-	V-2	-
032022	11	1.6 (0.06)	46 (1.81)	220 (49)	-40 (-40)	105 (221)	0 (32)	-	V-2	-
032022	1	1.6 (0.06)	46 (1.81)	220 (49)	-40 (-40)	105 (221)	0 (32)	-	-	-
032023	1	1.6 (0.06)	77 (3.03)	220 (49)	-40 (-40)	105 (221)	0 (32)	-	-	-
032023	11	1.6 (0.06)	77 (3.03)	220 (49)	-40 (-40)	105 (221)	0 (32)	-	V-2	-
032024	11	1.6 (0.06)	102 (4.02)	220 (49)	-40 (-40)	105 (221)	0 (32)	-	V-2	-

032024	1	1.6 (0.06)	102 (4.02)	220 (49)	-40 (-40)	105 (221)	0 (32)	-	-	-
032029	1	4.8 (0.19)	98 (3.86)	530 (119)	-40 (-40)	105 (221)	0 (32)	-	-	-
032029	11	4.8 (0.19)	98 (3.86)	530 (119)	-40 (-40)	105 (221)	0 (32)	-	V-2	-
032030	11	1.6 (0.06)	18 (0.71)	80 (18)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032030	1	1.6 (0.06)	18 (0.71)	80 (18)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032031	1	1.6 (0.06)	33 (1.30)	80 (18)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032031	11	1.6 (0.06)	33 (1.30)	80 (18)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032032	11	1.6 (0.06)	46 (1.81)	80 (18)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032032	1	1.6 (0.06)	46 (1.81)	80 (18)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032037	1	1.6 (0.06)	33 (1.30)	130 (29)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032037	11	1.6 (0.06)	33 (1.30)	130 (29)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032038	11	1.6 (0.06)	46 (1.81)	130 (29)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032038	1	1.6 (0.06)	46 (1.81)	130 (29)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032039	1	1.6 (0.06)	77 (3.03)	130 (29)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032039	11	1.6 (0.06)	77 (3.03)	130 (29)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032040	11	1.6 (0.06)	102 (4.02)	130 (29)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032040	1	1.6 (0.06)	102 (4.02)	130 (29)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032042	1	1.6 (0.06)	46 (1.81)	220 (49)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032042	11	1.6 (0.06)	46 (1.81)	220 (49)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032043	11	1.6 (0.06)	77 (3.03)	220 (49)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032043	1	1.6 (0.06)	77 (3.03)	220 (49)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032044	1	1.6 (0.06)	102 (4.02)	220 (49)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032044	11	1.6 (0.06)	102 (4.02)	220 (49)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032047	11	4.8 (0.19)	42 (1.65)	530 (119)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032047	1	4.8 (0.19)	42 (1.65)	530 (119)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032049	1	4.8 (0.19)	98 (3.86)	530 (119)	-40 (-40)	75 (167)	-10 (14)	-	-	-
032049	11	4.8 (0.19)	98 (3.86)	530 (119)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032050	11	4.8 (0.19)	218 (8.58)	530 (119)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-
032050	1	4.8 (0.19)	218 (8.58)	530 (119)	-40 (-40)	75 (167)	-10 (14)	-	V-2	-


Positioning Devices Investigated to ANSI/UL 1565



Catalog No.	Maximum Use Temp °C(°F)
6/6, 5, Slotted Cable Ducts (blue color)	
036200	50 (122)
036201	50 (122)
036202	50 (122)
036203	50 (122)
036205	50 (122)
036206	50 (122)
036207	50 (122)
036208	50 (122)
036211	50 (122)
036212	50 (122)
036213	50 (122)
036216	50 (122)
036217	50 (122)
036225	50 (122)
6/6, 5, Slotted Cable Ducts (gray color)	
636009	50 (122)
636014	50 (122)
636018	50 (122)
636022	50 (122)
636109	50 (122)
636114	50 (122)
636118	50 (122)
636122	50 (122)
636123	50 (122)
6/6, 5, Slotted Cable Ducts (gray color)	
636000	50 (122)
636001	50 (122)
636002	50 (122)
636005	50 (122)
636006	50 (122)
636007	50 (122)
636008	50 (122)
636011	50 (122)
636012	50 (122)
636013	50 (122)
636016	50 (122)
636017	50 (122)
636025	50 (122)
636095	50 (122)
636096	50 (122)
636100	50 (122)
636101	50 (122)
636102	50 (122)

636103	50 (122)
636105	50 (122)
636106	50 (122)
636107	50 (122)
636108	50 (122)
636111	50 (122)
636112	50 (122)
636113	50 (122)
636115	50 (122)
636116	50 (122)
636117	50 (122)
636119	50 (122)
636120	50 (122)
636121	50 (122)
636124	50 (122)
636125	50 (122)
Slotted Cable Ducts (gray color)	
636200	50 (122)
636201	50 (122)
636202	50 (122)
636206	50 (122)
636207	50 (122)
636208	50 (122)
636212	50 (122)
636213	50 (122)
636217	50 (122)
636225	50 (122)



Marking: Company name, catalog or model number, the Recognized Component Mark,  and, if published with the product, the product's maximum and minimum operating temperature, minimum installation temperature if below 0°C, minimum and maximum bundle diameter, loop tensile strength, type designation and/or declared mechanical strength on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2017-11-07

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".