

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Multiple cord extension set

Name and address of the applicant

LEGRAND FRANCE

128, avenue du Maréchal de Lattre de Tassigny B.P. 523,
87045 LIMOGES CEDEX - France

Name and address of the manufacturer

LEGRAND FRANCE

128, avenue du Maréchal de Lattre de Tassigny B.P. 523,
87045 LIMOGES CEDEX - France

Name and address of the factory

NINGBO BANMEN ELECTRIC APPLIANCE CO., LTD

East Industrial Zone, Guanhaiwei Cixi City , 315314 ZHEJIANG
PROVINCE - China

☐ Additional Information on page 2

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

MAX. 3680 W, 230 V~

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

G21 Series

References: 6 946 14, 6 946 19, 6 946 25, 6 946 30

Additional information (if necessary may also be reported on page 2)

Supersedes CBTC 679961 dated 27/05/2016 (Addition of product references ; update of the list of components)

☒ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60884-1:2002+A1:2006 +A2:2013


As shown in the Test Report Ref. No. which forms part of this Certificate

BAN-13MA0907ACSC, 126068-652764, LCI-16JA1539ATSS,
BAN-16NO1014ACSC

This CB Test Certificate is issued by the National Certification Body



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Date: 19/04/2017

Signature: **Jean-François BRUEL**
Certification Officer

ANNEX


RATING AND MAIN CHARACTERISTICS

Series	References	Number of sockets	Length of cable	Colour of enclosure	Additional function
G21 series	6 946 14	4	2 m	White / Grey	SPD / USB / MicroUSB
	6 946 19			Black	SPD / USB / MicroUSB
	6 946 25			Black / Aluminium painting	SPD / USB / MicroUSB / WIFI
	6 946 30			Black / Aluminium painting	SPD / USB / wireless charger

Standard Sheet:	III (CEE 7)
rated current (A)	16 A
rated load (W)	Max. 3680 W
rated voltage (V)	250 V~
household voltage (V)	230 V~
degree of protection	IP20
provision for earthing	with earthing contact
method of connecting the cable	non-rewirable
type of terminals	-
type of connections	soldered –welded–other
colour	white, grey, black, aluminium painting
socket-outlets	
multiple socket-outlets	6A :
number of socket-outlets	16A :4
degree of protection against electric shock	normal protection
existence of shutters	with shutters
method of application - mounting	portable type
method of installation	-
plugs:	
class of equipment	I
entry of cable	lateral



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Date: 19/04/2017


Signature: **Jean-François BRUEL**
Certification Officer

ANNEX

Components	Model	Manufacturer	Conformity
Plug	A14	Legrand France	VDE 40018331
Cable	H05VV-F	Legrand France	VDE 40017697
Switch	DPS05	Zhejiang Dawei Electrical Co., Ltd.	TÜV HN 69240463
	PS-5	Canal Electronic Co., Ltd.	VDE 40008318
	KAN-L6	Nova Electronics Co., Ltd.	TÜV R 50232848
	SC7097	Shenzhen Baokezhen Electronic Co., Ltd.	Intertek S 1610405
SPD	X17	Legrand France	LCIE test report No. LCI-16JA1529ATSS
USB charger	Xenon-USB2.4A-2 Xenon-USB2.4A-3		LCIE test report No.BAN- 16DE0631VTSC
Wireless charging	BAN-INDUCTION-1		LCIE test report No.BAN- 16DE1292VTSC
Wifi module	CN-M7628KR1		LCIE test report No.BAN- 17JA0154VTSC



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Date: 19/04/2017

Signature: **Jean-François BRUEL**
Certification Officer