

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

SHAVER TRANSFORMERS AND SHAVER SUPPLY UNITS

Name and address of the applicant

LEGRAND FRANCE
128, avenue du Maréchal de Lattre de Tassigny B.P. 523,
87045 LIMOGES CEDEX - France

Name and address of the manufacturer

LEGRAND FRANCE
128, avenue du Maréchal de Lattre de Tassigny B.P. 523,
87045 LIMOGES CEDEX - France

Name and address of the factory

LEGRAND (BEIJING) ELECTRICAL Co Ltd
N° 4 Chaoqian Road, Ke Ji Yuan Qu, Chang Ping District ,
102200 BEIJING - China

Note: When more than one factory, please report on page 2

 Additional Information on page 2

Ratings and principal characteristics

See annex 1

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

Series MALLIA
References : see annex 1

Additional information (if necessary may also be reported on page 2)

Supersedes CBTC FR 629874 dated 20/03/2013. Addition of product references


A sample of the product was tested and found to be in conformity with

IEC 61558-1:2005 +A1:2009 (ed.2)
IEC 61558-2-5:2010 (ed.2)

As shown in the Test Report Ref. No. which forms part of this Certificate

146128-698361

This CB Test Certificate is issued by the National Certification Body

LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr

Date: 26/01/2017

Signature: **Jean-François Bruel**
Certification Officer

ANNEX 1

REFERENCES, MAIN CHARACTERISTICS


Reference	Rated voltage		Other information
	supply	output	
2 811 35	230 V~	120/230 V~	White complete
2 821 35	230 V~	120/230 V~	Matt Black without plate
2 831 35	230 V~	120/230 V~	Silver without plate
2 833 35	230 V~	120/230 V~	Pearl without plate
2 835 35	230 V~	120/230 V~	Dark silver without plate
2 839 35	230 V~	120/230 V~	Champagne without plate

Frequency	50 / 60 Hz
Supply	230 V~
Output	120 / 230 V
Power output	20 VA
Class	I
Short-circuit protection	Non-inherently short-circuit proof
Degree of protection	IP24
Mobility	Stationary
Time of operation	Continuous
Intended use	Associated for specific use
Rated maximum ambient temperature	25°C
Windings	Class A
Output connection	Socket
Terminals (Supply)	Screwless

Cover Plate (2x1 gang)	
Reference	Other information
2 819 01	White
2 819 06	Silver
2 819 11	Champagne
2 819 51	Pearl
2 819 56	Dark silver
2 819 61	Brass
2 819 66	Bronze
2 819 71	Matt black
2 819 76	Copper
2 819 79	Metal BSS
2 819 83	Metal gold
2 819 87	Metal PSS
2 819 91	Metal Lacquered black



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Date: 26/01/2017

Signature: **Jean-François Bruel**
Certification Officer