



622 10



622 11



622 15

## 1. RANGE

622 10: E27 75W 230V inspection lamp Steel guard 10m cable

622 11: E27 75W 230V inspection lamp Steel guard 10m cable with switch and clamp

622 15: E27 75W 24V inspection lamp Steel guard 10m cable with HYPRA plug

## 2. CHARACTERISTICS

	622 10	622 11	622 15
<b>PLUG</b>	2P - 10/16 A	2P - 10/16 A	Hypra
<b>CABLE</b>			
• type	H05 RN-F	H07 RN-F	H05 RN-F
• cross-section	2 x 1	2 x 1	2 x 1
• length	10 m	10 m	10 m
<b>HANDLE</b>			
• colour	black: RAL 9017	black: RAL 9017	black: RAL 9017
• material	SEBS	SEBS	SEBS
• switch	no	yes	no
<b>CLAMP</b>	no	yes indemontable	no
• material	-	SEBS + PA66	-
• pivoting	-	yes	-
<b>GUARD</b>			
• material	rotary Rilsan steel	rotary Rilsan steel	rotary Rilsan steel
• colour	bright red: RAL 3020	bright red: RAL 3020	bright red: RAL 3020
• diameter	110 mm	110 mm	110 mm
• reflector	yes	yes	yes
• hook	yes	yes	yes
<b>LAMP HOLDER</b>			
• standard	E27	E27	E27
• material	PET	PET	PET
• I <sub>max</sub>	4 A	4 A	4 A
• power	75 W	75 W	75 W
• voltage	230 V	230 V	24 V
• frequency	50-60 Hz	50-60 Hz	0-60 Hz
<b>LAMP</b>			
• type	incandescent	incandescent	incandescent
• service life	1000 hr	1000 hr	1000 hr
• luminous flux	960 lm	960 lm	960 lm
• colour temp.	2600 K	2600 K	2600 K
<b>LAMP GLASS</b>			
• material	toughened glass	toughened glass	toughened glass

<b>Incandescent inspection lamps for professional use</b>	<b>Technical sheet : F0015C</b>
-----------------------------------------------------------	---------------------------------

Cat. No(s) : 622 10/11/15/16/17

Date : 01/04/03

**2. CHARACTERISTICS** (continued)

SAFETY			
<ul style="list-style-type: none"> <li>• IP</li> <li>• class</li> <li>• approvals</li> <li>• removable</li> <li>• CE conformity</li> </ul>	45 2 ENEC pending no yes	45 2 ENEC pending no yes	45 2 ENEC pending no yes
GENERAL CHARACTERISTICS			
<ul style="list-style-type: none"> <li>• total height</li> <li>• weight</li> <li>• type of packaging</li> <li>• pack quantity</li> <li>• pack size</li> <li>• pack L x W x H</li> <li>• Barcode (EAN13)</li> <li>• Customs code</li> </ul>	300 mm 1420 g cardboard box 1 / 5 6.5 dm <sup>3</sup> 345 x 150 x 127 3245060622107 940540950009D	300 mm 1820 g cardboard box 1 / 5 6.5 dm <sup>3</sup> 392 x 202 x 115 3245060622114 940540950009D	300 mm 1619 g cardboard box 1 / 5 6.5 dm <sup>3</sup> 392 x 202 x 115 3245060622152 940540950009D
ACCESSORIES			
<ul style="list-style-type: none"> <li>• pivoting clamp</li> <li>• spare lamp glass</li> </ul>	no 62247	no 62247	no 62247
PP = Polypropylene PA = Polyamide (Nylon ®, Rilsan ®) PC = Polycarbonate PET = Polyethylene terephthalate PBT = Polybutylene terephthalate			