

# Atlantic metal cabinets

IP 55/IP 66 - IK 10 - Nema 4x - Nema 12



TÜV



0 355 23



0 355 37



Plain plates, Lina 12.5 and Lina 25 perforated plates

p. 276

Cabinet and equipment selection chart **p. 262-263**  
 Technical characteristics **p. 266**

IP 66 according to standards IEC EN 60529 for 1 doors cabinets  
 IP 55 according to standards IEC EN 60529 for 2 doors cabinets  
 IK 10 according to standards IEC EN 62262  
 LCIE 17 07 90 10A  
 Nema 4x, 1 door, Nema 12, 2 doors - UL, CSA, Bureau Veritas, TÜV, GÖST agreements  
 EMC attenuation 20 dB (for an EMC attenuation from 40 to 50 dB at 1 GHz, please consult us)  
 Excellent resistance to corrosion and chemical agents  
 80 µm thick textured polyester coating. Anti-corrosion treatment for hinges and axis  
 Reversible door - One locking point. Locking with key 2433 A (2 keys supplied)  
 Up to 300 mm height, fitted with latch for height upper than 300 mm, fitted with lever  
 Low cable entries RAL 7035  
 Optional depth regulation for cabinets 400 mm depth Cat.No 0 367 45 (p. 265)

Pack	Cat.Nos	Metal cabinets vertical version		
		External dimensions (mm) Height x Width x Depth	Number of doors	Weight (kg)
1	0 355 09 <sup>1</sup>	400 x 300 x 150	1	6.3
1	0 355 00 <sup>2</sup>	300 x 200 x 160	1	4.2
1	0 355 02	400 x 300 x 200	1	6.5
1	0 355 03	500 x 400 x 200	1	9.7
1	0 355 04	600 x 400 x 200	1	10.7
1	0 355 07	500 x 400 x 250	1	10.7
1	0 355 08	600 x 400 x 250	1	12
1	0 355 12	700 x 500 x 250	1	16.5
1	0 355 14	800 x 600 x 250	1	18.8
1	0 355 17	1000 x 600 x 250	1	24
1	0 355 18	1000 x 800 x 250	1	36.4
1	0 355 22	700 x 500 x 300	1	23
1	0 355 23	800 x 600 x 300	1	28.8
1	0 355 26	1000 x 600 x 300	1	33.3
1	0 355 27	1000 x 800 x 300	1	42
1	0 355 92	1200 x 800 x 300	1	49.6
1	0 355 93	1200 x 1000 x 300	2	62.2
1	0 355 95	1400 x 1000 x 300	2	71
1	0 355 28	800 x 600 x 400	1	31
1	0 355 29	1000 x 800 x 400	1	45
1	0 355 96	1200 x 800 x 400	1	57
1	0 355 98	1400 x 800 x 400	1	64

Pack	Cat.Nos	Metal cabinets square version		
		External dimensions (mm) Height x Width x Depth	Number of doors	Weight (kg)
1	0 355 05 <sup>1</sup>	300 x 300 x 160	1	4.1
1	0 355 30	300 x 300 x 200	1	4.2
1	0 355 31	400 x 400 x 200	1	7.7
1	0 355 32	500 x 500 x 250	1	11.5
1	0 355 10	600 x 600 x 250	1	16.3
1	0 355 15	800 x 800 x 250	1	21.6
1	0 355 20	600 x 600 x 300	1	21.1
1	0 355 24	800 x 800 x 300	1	34.2
1	0 355 91	1000 x 1000 x 300	2	53
1	0 355 94	1200 x 1200 x 300	2	70
1	0 355 36	600 x 600 x 400	1	28
1	0 355 97	1200 x 1200 x 400	2	77

Pack	Cat.Nos	Metal cabinets horizontal version		
		External dimensions (mm) Height x Width x Depth	Number of doors	Weight (kg)
1	0 355 01	300 x 400 x 200	1	6.5
1	0 355 06	400 x 600 x 250	1	11.7
1	0 355 33	800 x 1000 x 250	2	27
1	0 355 21	600 x 800 x 300	2	28.8
1	0 355 37	600 x 1000 x 300	2	32
1	0 355 34	800 x 1000 x 300	2	33.3
1	0 355 90	1000 x 1200 x 300	2	62.2

**Roofs RAL 7035**

Steel  
 Possible adjustment ± 20 mm (front or back)

For cabinets		Weight (kg)
Width (mm)	Depth (mm)	
300	200	1.2
400	200	1.4
400	250	1.8
500	250	2
600	250	2.5
600	300	3
800	300	3.6

Pack	Cat.Nos	Lighting kit
1	0 363 12	Supplied with 8 W fluorescent tube, Ø16 mm 230 V - 50 Hz Class I - IP 20 - 600 lumens Electromagnetic compatibility according to EN 55015 Equipped with a switch Connection on terminal block Dim.: 320 x 61 x 32 mm

**Door contact** (p. 278)

1: With no opening  
 2: With no opening supplied with plain pates