

line taps and equipotential bonding connectors



0 340 03



0 340 33



0 340 42



0 340 45



0 343 85

Pack	Cat.Nos	Line taps	
		Strip of 10 separable line taps	
		Capacity per tap (mm ²)	Width (mm)
10	0 340 00	2 x 6	15
10	0 340 01	2 x 10	19.5
10	0 340 02	2 x 16	21
10	0 340 03	2 x 25	21.5
10	0 340 04	2 x 35	25

		Non-shear line taps			
		Hexagonal head			
		Capacity per tap (mm ²)	Width of slot (max. cable Ø in mm)	Overall height (mm)	Fixing centres (mm)
20	0 340 33	2 x 25	7.4	49	
10	0 340 34	2 x 50	9.5	59	
20	0 340 42	2 x 16	5.8	41	37
20	0 340 43	2 x 25	7.4	49	37
10	0 340 44	2 x 50	9.5	59	44
10	0 340 45	2 x 75	11.7	71	62


		Equipotential bonding connectors		
		Used to make equipotential connections on the installation busbar systems		
		Safe, intuitive 1/4 turn mounting ensuring an excellent, lasting equipotential link		
		Busbar system		Max. connection cross-section (mm)
		Ø min. (mm)	Ø max. (mm)	
20	0 343 85	12	16	6
10	0 343 86	18	22	16
10	0 343 87	28	32	16

equipotential bonding connectors

■ Screwless connections terminals

Connection terminals Nylbloc auto Cat.Nos 0 343 22/23/25/28

Ambient temperature: - 25 °C to + 55 °C (T55)
Self-extinguishing: 960 °C according to EN 60695-2-11
Low fire hazard



Use



Cat.No 0 343 99 tool for cable desheating and rapid wire stripping



Test via IP 2X test tip
Cat.No 0 394 45




Plexo box with support
Cat.No 0 343 98 directly fixed on top part



Trunking adaptable DLP with support
Cat.No 0 343 98 directly fixed

■ Characteristics

- Resistance to incandescent wire 960°C
- Resistivity ≤ 0.4 m Ω
- Polyamide
- Grey



Cat.Nos	Dimensions (mm)			
	A	B	C	D
0 343 85	24	8	40.5	31.5
0 343 86	24	9	49	40
0 343 87	24	11	59	46.5


■ Installation




1 Fixed with a quarter turn



2 Held in place by a stainless steel spring blade



3 Final locking with 5.5 mm screwdriver



4 Connecting the equipotential bonding with a through and/or terminating connection