

Mosaic™ Programme mechanisms

international standards socket outlets



0 775 02



0 775 04




0 775 05



0 775 06



0 770 80



Selection chart for boxes, supports and plates p. 882-883

Pack	Cat.Nos	Other standard socket outlets
10	0 775 01	Euro-US standard - white 1 module
10	0 775 02	2 modules
10	0 775 03	US standard - white 1 module
10	0 775 04	2 modules - 15 A
10	0 775 05	British standard - white 2 modules - 13 A
10	0 775 10	Italian type - white 1 module - 10 A - screw terminals
10	0 775 11	1 module - 10/16 A - screw terminals
10	0 775 12	1 module - 16 A - screw terminals
10	0 775 06	Swiss type - white 2 modules - type 13
10	0 775 08	Danish standard - white 2 modules - with shutters for child protection
10	0 775 09	2 modules - for UPS - with shutters for child protection

NEW

Pack	Cat.Nos	2P ELV socket outlet
10	0 771 50	With shutters for child protection For installation in flush-mounting box, surface-mounting box, floor box, column module, desktop multi-outlet extension, office module and trunking 1 module - white antimicrobial

Pack	Cat.Nos	Anti-extraction module
1	0 770 80	When used with a socket, avoids accidental unplugging of sensitive electrical equipment, by gripping the cord (Ø4 to 8 mm cords) Can withstand an extraction force of 350 N (35 kgs) 1 module - white antimicrobial

Mosaic™ Programme mechanisms

USB sockets for charging

NEW



0 775 94



0 775 91



0 793 93



Selection chart for supports and plates p. 882-883

Average charging time for devices equipped with lithium-ion polymer batteries:

- 80% charged < 2h
- 100% charged < 4h

No specific constraint: no need to wait for the battery to be flat before charging it, or to have it fully charged before use

Pack	Cat.Nos	USB power supplies
		For recharging portable devices Conform to IEC 62684-2011-01 Consumption in passive mode < 0.3 W 2P+E tap-off connection via 2.5 mm ² screw terminals Supplied cordless
		Double USB sockets - 5V- 1500 mA For telephones, smartphones, MP3/MP4 players and fast-charging tablet PC 2 modules
5	0 775 94	<ul style="list-style-type: none"> ○ White ● Alu
1	0 793 94	
		Single USB sockets - 5V - 750 mA For telephones and smartphones 1 module
10	0 775 91	<ul style="list-style-type: none"> ○ White ● Alu
1	0 793 91	

January 2014

Pack	Cat.Nos	USB power supplies with retractable cord
		For recharging portable devices such as telephones and smartphones Single socket 5 V - 750 mA equipped with a retractable cord with micro USB connector Conform to IEC 62684-2011-01 Consumption in passive mode < 0.3 W 2P+E tap-off connection via 2.5 mm ² screw terminals Cord length : 0.32 m
10	0 775 93	<ul style="list-style-type: none"> ○ White ● Alu
10	0 793 93	

January 2014

Pack	Cat.Nos	Support for portable device on charge
1	0 803 99	Prevents device from any fall risk and allows secure use of device while charging Wall-mounting Fixing tools supplied For 1 portable device Supplied with a mobile retractable cord