



0 414 62



0 413 49



0 414 19



0 415 23



0 415 33 with claws



0 413 98

Pack	Cat.Nos	Class I			
		Double insulated Polyester corrosion resistant finish 200 hours maxi. continuous rating			
		IP 44 - IK 10 - Direct current version Ø150 mm gong			
1	RAL 3000 Red 0 414 62	Voltage = 24 V	Average Consumption (mA) 70	Average acoustic output at 1 m (dB) 90	Weight (kg) 1
		IP 40 - IK 08 - 50/60 Hz - Alternating current version Ø100 mm gong			
1	RAL 7037 Grey 0 413 49	Voltage ~ 230 V	Consumption (mA) 50	Average acoustic output at 1 m (dB) 95	Weight (kg) 0.8
		IP 44 - IK 10 Ø150 mm gong			
1	0 414 16	24V	360	98	1
1	0 414 18	110/130 V	90	98	1
1	0 414 19	230 V	50	98	1
		IP 44 - IK 10 Ø250 mm gong			
1	0 414 39	230 V	70	98	2.1

Technical characteristics and chart of sounds [see e-catalogue](#)

Pack	Cat.Nos	Industrial warning devices 110 dB IP 20 - IK 08		
		Frequency 350/400 Hz, continuous sound Operates intermittently: 1 min on / 10 min off		
1	0 415 20	24 V~ and = power supply 230 V~ power supply	Consumption in mA	
1	0 415 23		820	120

		Electromechanical sirens IP 30 - IK 05				
		Supplied with screws for semi-flush mounting				
		D.C. current				
		Voltage =	Power (W)	Consumption (mA)	Average acoustic output at 1 m (dB)	Max. continuous rating (hr)
1	0 415 32	12 V	11	889	98	200
1	0 415 33	24 V	12	516	100	200
		A.C. current - 50/60 Hz				
		Voltage ~	Power (W)	Consumption (mA)	Average acoustic output at 1 m (dB)	Max. continuous rating (hr)
1	0 415 36	24 V	12.5	531	100	200
1	0 415 38	110 V	70	400	105	100
1	0 415 39	230 V	57	250	105	100

		Multi-sound electronic sirens
		To be equipped with base for LED beacons and multi-sound electronic sirens Cat.Nos 0 413 81/82/83 (p. 395) 64 electronic sounds possible, 2 channels Configuration by microswitches Adjustable sound level from 87 to 100 dB (1m) Dimensions: Ø92 mm x 60 mm Power supply from 12 V~ and = to 230 V~ depending on the installed base IP 65 - IK 08
1	0 413 98	