

MCBs DX³ - 36 kA

thermal magnetic MCBs from 10 A to 80 A - C curve



Technical characteristics [see e-catalogue](#)

Breaking capacity:
36 kA - IEC 60947-2 - 400 V \sim
Can be equipped with DX³ auxiliaries and accessories (p. 72)

Pack	Cat.Nos	2-pole - 230/400 V \sim	
	C curve	Nominal rating I _n (A)	Number of modules
1	4 100 07	10	3
1	4 100 08	16	3
1	4 100 09	20	3
1	4 100 10	25	3
1	4 100 11	32	3
1	4 100 12	40	3
1	4 100 13	50	3
1	4 100 14	63	3
1	4 100 15	80	3

Pack	Cat.Nos	3-pole - 400 V \sim	
	C curve	Nominal rating I _n (A)	Number of modules
1	4 100 20	10	4.5
1	4 100 21	16	4.5
1	4 100 22	20	4.5
1	4 100 23	25	4.5
1	4 100 24	32	4.5
1	4 100 25	40	4.5
1	4 100 26	50	4.5
1	4 100 27	63	4.5
1	4 100 28	80	4.5

Pack	Cat.Nos	4-pole - 400 V \sim	
	C curve	Nominal rating I _n (A)	Number of modules
1	4 100 33	10	6
1	4 100 34	16	6
1	4 100 35	20	6
1	4 100 36	25	6
1	4 100 37	32	6
1	4 100 38	40	6
1	4 100 39	50	6
1	4 100 40	63	6
1	4 100 41	80	6

MCBs DX³ - 50 kA

thermal magnetic MCBs from 10 A to 63 A - C and D curves



Technical characteristics [see e-catalogue](#)

Breaking capacity:
50 kA - IEC 60947-2 - 400 V \sim
Can be equipped with DX³ auxiliaries and accessories (p. 72)

Pack	Cat.Nos	Single pole 230/400 V \sim	
	C curve D curve	Nominal rating I _n (A)	Number of modules
1	4 101 34 4 101 86	10	1.5
1	4 101 35 4 101 87	16	1.5
1	4 101 36 4 101 88	20	1.5
1	4 101 37 4 101 89	25	1.5
1	4 101 38 4 101 90	32	1.5
1	4 101 39 4 101 91	40	1.5
1	4 101 40 4 101 92	50	1.5
1	4 101 41 4 101 93	63	1.5

Pack	Cat.Nos	2-pole - 230/400 V \sim	
	C curve D curve	Nominal rating I _n (A)	Number of modules
1	4 101 47 4 101 99	10	3
1	4 101 48 4 102 00	16	3
1	4 101 49 4 102 01	20	3
1	4 101 50 4 102 02	25	3
1	4 101 51 4 102 03	32	3
1	4 101 52 4 102 04	40	3
1	4 101 53	50	3
1	4 101 54	63	3

Pack	Cat.Nos	3-pole - 400 V \sim	
	C curve D curve	Nominal rating I _n (A)	Number of modules
1	4 101 60 4 102 12	10	4.5
1	4 101 61 4 102 13	16	4.5
1	4 101 62 4 102 14	20	4.5
1	4 101 63 4 102 15	25	4.5
1	4 101 64 4 102 16	32	4.5
1	4 101 65 4 102 17	40	4.5
1	4 101 66 4 102 18	50	4.5
1	4 101 67 4 102 19	63	4.5

Pack	Cat.Nos	4-pole - 400 V \sim	
	C curve D curve	Nominal rating I _n (A)	Number of modules
1	4 101 73 4 102 25	10	6
1	4 101 74 4 102 26	16	6
1	4 101 75 4 102 27	20	6
1	4 101 76 4 102 28	25	6
1	4 101 77 4 102 29	32	6
1	4 101 78 4 102 30	40	6
1	4 101 79 4 102 31	50	6
1	4 101 80 4 102 32	63	6