

# Switching mode power supplies

single-phase



# Power supplies with battery back-up



1 467 01

1 467 12

1 467 22

Technical characteristics **see e-catalogue**

Conform to standards UL 508, UL 60950, EN 61558-2-16 and IEC EN 60950-1, EN 55022 class B, EN 61000-3-2, EN 61000-3-3, EN 61000-6-2 and EN 61204-3  
 Operating frequency: 50/60 Hz  
 Output voltage present indicator  
 Output voltage adjustment potentiometer on front panel  
 Integrated short-circuit and overload protection  
 For mounting on a symmetrical rail depth 7.5 mm and 15 mm

Pack	Cat.Nos	Single-phase - 12 - 92 W			
		No-load power consumption < 0.3 W Adjustable output voltage			
		<b>Input voltage: 100 to 240 V<math>\sim</math></b> <b>Output voltage: 5 V<math>\equiv</math></b>			
		Nominal power (W)	Rated current (A)	Setting range (V)	Number of modules
1	1 467 01	12	2.4	4.5 to 5.5	1
		<b>Input voltage: 100 to 240 V<math>\sim</math></b> <b>Output voltage: 12 V<math>\equiv</math></b>			
1	1 467 11	24	2	10.8 to 13.8	2
1	1 467 12 <sup>1</sup>	54	4.5	10.8 to 13.8	3
		<b>Input voltage: 100 to 240 V<math>\sim</math></b> <b>Output voltage: 24 V<math>\equiv</math></b>			
1	1 467 21	15	0.6	21.6 to 29	1
1	1 467 22	36	1.5	21.6 to 29	2
1	1 467 23 <sup>1</sup>	60	2.5	21.6 to 29	3
1	1 467 24 <sup>1</sup>	92	3.8	24 to 25.5	4

1: Double output terminal block



0 042 10

Dimensions **see e-catalogue**

For supplying PLCs and their peripherals or any use requiring a voltage of 12 V $\equiv$   
 Fixing on rail

Pack	Cat.Nos	Power supplies with battery back-up		
		Conform to standards IEC/EN 61558-2-6, EN 55022 (class B), EN 61000-4-2 With "ON"/"OFF" button, operation indicator, fuse protection Power supply 230 V $\sim$		
		<b>12 V<math>\equiv</math></b> Capacity 280 mA/h		
		Power (W)	Current (A)	Number of modules
1	0 042 10	6	0.5	6