

XL³ S 160 - 24 modules per row

“ready to use” metal distribution cabinets



3 372 04



3 372 24

Technical characteristics p. 229

Cabinets supplied with rails fitted (150 mm fixing centres) and full height faceplates
 Doors and terminal blocks to be ordered separately
 Take DPX³ 160 and modular protection devices
 Used to create assemblies certified IEC 61439-2 and -3
 IP 40 with door
 IP 30 without door
 Cut-outs in top and bottom for feeding cables through
 Can take Lina 25 ducting

Pack Cat.Nos Surface mounting 24-module per row cabinets

Pack	Cat.Nos	Number of rows	Number of modules	Height (mm)	Width (mm)	Depth (mm)	Faceplates and body: RAL 9003
1	3 372 02	2	48	440	595	135	
1	3 372 03	3	72	590	595	135	
1	3 372 04	4	96	740	595	135	
1	3 372 05	5	120	890	595	135	
1	3 372 06	6	144	1040	595	135	
1	3 372 07	7	168	1190	595	135	
1	3 372 08	8	192	1340	595	135	

Pack Cat.Nos Flush-mounting 24-module per row cabinets

Pack	Cat.Nos	Number of rows	Number of modules	Height (mm)	Width (mm)	Depth (mm)	Supplied with fixing lugs Faceplates: RAL 9003
1	3 372 22	2	48	512	667	138	
1	3 372 23	3	72	662	667	138	
1	3 372 24	4	96	812	667	138	
1	3 372 25	5	120	962	667	138	
1	3 372 26	6	144	1112	667	138	
1	3 372 27	7	168	1262	667	138	
1	3 372 28	8	192	1412	667	138	