


# Viking™ 3 power terminal blocks




Approvals **p. 919**

Bridging the gap between the enclosure and external cables

Pack	Cat.Nos	<b>Insulated aluminium/copper power terminal blocks</b>		
		For aluminium/copper cables, copper bars or cable lugs (see selection chart p. 339) Direct connection of cable Insulation and protection against direct contact without additional accessories (built-in dividers and covers) Pre-cut removable covers for adjustment to the various connection modes Fixed using metal clip for rails $\lrcorner$ 15 mm depth and $\lrcorner$ EN 60715 15 mm depth, or on plate with screws Permits the use of Cab 3, Duplix markers Test via test plug closed covers Blocks with identical pitch can be joined using a threaded rod Shunting possible with Cat.Nos 0 394 46/47		
5	0 390 10	Rigid or flexible cable (mm <sup>2</sup> )	Rigid or flexible cable (mm <sup>2</sup> )	Pitch (mm)
5	0 390 11	Al/Cu 35 to 120	Cu 35 to 70	42
5	0 390 13	Al/Cu 95	Al/Cu 95	36
5	0 390 14	Al/Cu 150	Al/Cu 150	42
5	0 390 15	Al/Cu 300	Al/Cu 300	55
5	0 390 17	Al/Cu 150	Cu 35 to 95	42
5	0 390 18	Al/Cu 300	Cu 70 to 150	55
5	0 390 20	Al/Cu 35 to 120	Al/Cu 120	42
5	0 390 21	Al/Cu 70 to 300	Al/Cu 300	55
		<b>Equipotential bonding shunts</b>		
5	0 394 46	For insulated aluminium/copper power terminal blocks		
5	0 394 47	Supplied with screws		
		For blocks with pitch 36 and 42 mm		
		For blocks with pitch 55 mm		

Pack	Cat.Nos	<b>Bare power terminal blocks</b>	
		For copper bars or cable lugs Insulation dividers and protective covers to be ordered separately For use with terminal marker sheets (p. 342)	
		<b>Cable lug - cable lug for symmetrical rails</b>	
		Fixed using metal clip on rails $\lrcorner$ 15 mm depth and $\lrcorner$ EN 60715 15 mm depth	
		Connecting max. (mm <sup>2</sup> )	Pitch (mm)
5	0 390 71	35	26
5	0 390 72	70	34
5	0 390 73	120	34
5	0 390 74	240	46
		<b>Cable lug - cable lug for asymmetrical rails</b>	
		Fixed using metal clip on rails $\lrcorner$ EN 60715	
5	0 390 31	35	26
5	0 390 32	70	34
5	0 390 33	120	34
5	0 390 34	240	46
		<b>Insulation and protection accessories</b>	
		For bare power terminal blocks	
		<b>Separation barriers</b>	
		Take protective covers	
		Marking possible with CAB 3 (p. 342)	
10	0 394 77	For blocks with pitch 26 mm	
10	0 394 78	For blocks with pitch 34 and 46 mm	
		<b>Protective covers</b>	
		For mounting on separation barriers	
5	0 394 86	For 3 blocks with pitch 46 mm or for 4 blocks with pitch 34 mm	
5	0 394 88	For 4 blocks with pitch 26 mm	
5	0 394 89	For 4 blocks with pitch 46 mm	



End stops  
**p. 332**

Al/Cu distribution boxes  
**p. 203**

CAB 3 marking system  
**p. 342**