


 Support frame and plate selection charts **p. 480-487**

Mechanisms supplied with rocker plates, to be equipped with support frames (p. 476) and plates (p. 480 to 487)

Pack	Cat.Nos	HDMI type A sockets
1	5 720 96	Used to transmit high-definition digital audio/video streams between a source (Blu-ray player, computer) and a compatible receiver (TV, videoprojector...) Preterminated sockets HDMI 1.4 - 1 module Equipped with cord, length 15 cm ○ White ● Magnesium
1	5 725 96	
1	5 724 76	Preterminated sockets HDMI 1.4 - 2 modules Equipped with cord, length 15 cm ○ White ● Magnesium
1	5 735 96	
1	5 722 81 ¹	Screw-type sockets HDMI 1.3 - 2 modules ○ White ● Magnesium
1	5 727 81 ¹	
1	0 517 38	HDMI extender Extends HDMI audio/video signals up to 57 m at up to a 4 K resolution using HD BaseT Lite technology Kit includes both transmitter and receiver with link via a network cord RJ 45/RJ 45(p. 402) Supports 3D video, HDCP, 4K resolution, EDID passthrough and IR control, HD BaseT certified
1	5 720 90	Display port sockets Used to transmit high-definition digital audio/video streams between a source (laptop, computer, etc) and a compatible receiver (TV, videoprojector...) Preterminated socket - 1 module Equipped with cord, length 15 cm ○ White ● Magnesium
1	5 725 90	

Pack	Cat.Nos	HD15 sockets
1	5 720 97	Used to transmit analog video streams (VGA, XGA, UXGA depending on graphic card) between a source (computer) and a compatible receiver (LCD, video projector, TV, etc...) Preterminated sockets - 1 module Equipped with cord, length 15 cm ○ White ● Magnesium
1	5 725 97	
1	5 722 82 ¹	Screw-type female HD15 sockets - 2 modules ○ White ● Magnesium
1	5 727 82 ¹	
1	5 722 88	Screw-type female HD15 + 3.5 mm Jack sockets - 2 modules ○ White ● Magnesium
1	5 727 88	
1	5 722 79	Solder-type female HD15 sockets - 1 module 15 pin ○ White ● Magnesium
1	5 727 79	
1	5 720 89	Videoprojector switch Universal remote switch allowing to turn ON or place in STANDBY mode a video projector Works with all videoprojectors or TV through IR learning process Installed close to the room's lighting switches, it replaces the constructors remote and fosters the ignition and extinction of the video projector therefore reducing energy consumption and extending the bulb's lifetime Equipped with cord, length 15 cm ○ White

1: Can be installed in receptacles for floor sockets p. 479

 Floor sockets see **p. 479**

 Audio/Video patch panels, cables and cords, **p. 755-756**

 USB data sockets see **p. 470**
