

Synergy™

British standard socket outlets - Authentic



Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

GG: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries. Compact mechanism for maximum wiring space

Pack	Cat.Nos	Socket outlets 13 A - 250 V \sim
		Conform to BS 1363: Part. 2 With safety shutter mechanism For flush-mounting, back box to be min. 25 mm deep ASTA licence
		1 gang unswitched Nominal plate dimensions: 86 x 86 mm
1	8 330 65	● Brushed stainless steel
1	8 332 65	● Polished stainless steel
1	8 334 65	● Glossy gold
		2 gang unswitched Nominal plate dimensions: 86 x 146 mm
1	8 330 75	● Brushed stainless steel
1	8 332 75	● Polished stainless steel
1	8 334 75	● Glossy gold

Pack	Cat.Nos	Single pole socket outlets 13 A - 250 V \sim
		Conform to BS 1363: Part. 2 With safety shutter mechanism For flush-mounting, back box to be min. 25 mm deep ASTA licence
		1 gang switched Nominal plate dimensions: 86 x 86 mm
1	8 330 66	● Brushed stainless steel
1	8 332 66	● Polished stainless steel
1	8 334 66	● Glossy gold
		1 gang switched with blue LED power indicator Nominal plate dimensions: 86 x 86 mm
1	8 330 67	● Brushed stainless steel
1	8 332 67	● Polished stainless steel
1	8 334 67	● Glossy gold
		2 gang switched Nominal plate dimensions: 86 x 146 mm
1	8 330 76	● Brushed stainless steel
1	8 332 76	● Polished stainless steel
1	8 334 76	● Glossy gold
		2 gang switched with blue LED power indicator Nominal plate dimensions: 86 x 146 mm
1	8 330 77	● Brushed stainless steel
1	8 332 77	● Polished stainless steel
1	8 334 77	● Glossy gold

Pack	Cat.Nos	Single pole socket outlets 13 A - 250 V \sim with USB charger
		Conform to BS 1363-2 USB charger conform to IEC 60950-1
		1 gang switched USB Type-A 2.4 A - 5 V \equiv - 12 W Consumption in passive mode < 0.08 W
1	8 330 78	● Brushed Stainless steel
1	8 332 78	● Polished Stainless steel
1	8 334 78	● Glossy gold
		2 gang switched USB Type-A + Type-C™ 3 A - 5 V \equiv - 15 W Consumption in passive mode < 0.08 W
1	8 330 79	● Brushed Stainless Steel
1	8 332 79	● Polished Stainless Steel
1	8 334 79	● Glossy Gold

Pack	Cat.Nos	Double pole socket outlets 13 A - 250 V \sim
		Conform to BS 1363: Part. 2 With safety shutter mechanism For flush-mounting, back box to be min. 25 mm deep ASTA licence
		1 gang switched Nominal plate dimensions: 86 x 86 mm
1	8 330 60	● Brushed stainless steel
1	8 332 60	● Polished stainless steel
1	8 334 60	● Glossy gold
		1 gang switched with blue LED power indicator Nominal plate dimensions: 86 x 86 mm
1	8 330 61	● Brushed stainless steel
1	8 332 61	● Polished stainless steel
1	8 334 61	● Glossy gold
		2 gang switched Nominal plate dimensions: 86 x 146 mm
1	8 330 70	● Brushed stainless steel
1	8 332 70	● Polished stainless steel
1	8 334 70	● Glossy gold
		2 gang switched with blue LED power indicator Nominal plate dimensions: 86 x 146 mm
1	8 330 71	● Brushed stainless steel
1	8 332 71	● Polished stainless steel
1	8 334 71	● Glossy gold
		2 gang switched outboard for standard and clean earth applications Nominal plate dimensions: 86 x 146 mm
1	8 330 74	● Brushed stainless steel
1	8 332 74	● Polished stainless steel
1	8 334 74	● Glossy gold