



8 334 89



8 330 69



8 332 59



8 330 44

Slim front plate:

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

GG: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos	Socket outlets 15 A - 250 V~
		Conform to BS 546 Patented 3 pin safety shutter mechanism, For flush-mounting, back box to be min. 35 mm deep Nominal plate dimensions: 86 x 86 mm
1	8 330 88	1 gang unswitched
1	8 332 88	● Brushed stainless steel
1	8 334 88	● Polished stainless steel
		● Glossy gold
1	8 330 89	1 gang switched - single pole
1	8 332 89	● Brushed stainless steel
1	8 334 89	● Polished stainless steel
		● Glossy gold

Pack	Cat.Nos	Socket outlets 15 A - 127 V~
		For flush-mounting, back box to be min. 35 mm deep
1	8 330 99	1 gang
1	8 334 99	Nominal plate dimensions: 86 x 86 mm
1	8 333 99	● Brushed stainless steel
		● Polished stainless steel
		● Glossy gold
1	8 332 99	2 gang
1	8 331 99	Nominal plate dimensions: 86 x 146 mm
1	8 335 99	● Brushed stainless steel
		● Polished stainless steel
		● Glossy gold

Pack	Cat.Nos	Socket outlets 5 A - 250 V~
		Conform to BS 546 Patented 3 pin safety shutter mechanism, For flush-mounting, back box to be min. 25 mm deep
1	8 330 68	1 gang unswitched
1	8 332 68	Nominal plate dimensions: 86 x 86 mm
1	8 334 68	● Brushed stainless steel
		● Polished stainless steel
		● Glossy gold
1	8 330 69	1 gang switched - single pole
1	8 332 69	Nominal plate dimensions: 86 x 146 mm
1	8 334 69	● Brushed stainless steel
		● Polished stainless steel
		● Glossy gold

Pack	Cat.Nos	Socket outlets 2 A - 250 V~
		Conform to BS 546 For flush-mounting, back box to be min. 25 mm deep Nominal plate dimensions: 86 x 86 mm
1	8 330 59	1 gang unswitched
1	8 332 59	Nominal plate dimensions: 86 x 86 mm
1	8 334 59	● Brushed stainless steel
		● Polished stainless steel
		● Glossy gold

Pack	Cat.Nos	Double USB sockets
		For flush-mounting, back box to be min. 40 mm deep Input voltage: 110 V/ 230 V Comply with IEC 62684 5 V (output) - 2400 mA Wiring with 1.5 mm ² and 2.5 mm ² (only live and neutral)
1	8 330 44	Double USB sockets
1	8 332 44	● Brushed stainless steel
1	8 334 44	● Polished stainless steel
		● Glossy gold