

Mosaic™ Programme mechanisms

keyswitches, emergency stop pushbuttons, keycard switches, hotel bedroom indicators, shaver socket



0 770 72



0 770 75



0 766 01



0 770 47

Selection chart for boxes, supports and plates **p. 900-901**

Pack	Cat.Nos	Keyswitches
1	0 770 72	<p>2 modules</p> <p>2-position switch By changeover contact 6 A - 250 V~ RONIS key no. 601 Key can be removed in both positions ○ White</p>
1	0 770 73	<p>3-position switch Changeover switch with OFF position 6 A - 250 V~ RONIS key no. 601 Key can be removed in all 3 positions ○ White</p>
1	0 770 74	<p>2-position switch - European key barrel 1 contact - 2 poles 10 A - 250 V~ Key extracted in central position without changing the status of the contacts ON/OFF Must be fitted with standard European key barrel or key barrel Cat.No 0 697 95 ○ White</p>
1	0 770 75	<p>3-position pushbutton - European key barrel Changeover switch with OFF position 10 A - 250 V~ Key extracted in OFF position Must be fitted with standard European key barrel or key barrel Cat.No 0 697 95 ○ White</p>
1	0 697 95	<p>European key barrel European key barrel supplied with one set of 3 keys </p>

Pack	Cat.Nos	Emergency stop mushroom head pushbuttons
1	0 766 01	<p>2 modules</p> <p>With key NO + NC 3 A - 250 V~ Unlock with RONIS key no. 455 ● Red/yellow</p>
1	0 766 02	<p>1/4 turn NO + NC 3 A - 250 V~ 1/4 turn unlocking ● Red/yellow</p>

Pack	Cat.Nos	Keycard switches
1	0 767 28	<p>For energizing a circuit by inserting an ISO format card (e.g: Cat.No 0 767 11 or hotel room access card) Time-delay: 30 sec. after card removal Backlight insert badge area 2 modules</p> <p>Electronic keycard switches Only operates with MIFARE contactless ISO badge cards (e.g Cat.Nos 0 767 11/12/13) Contact capacity: - 110 V, power 15 VA - 230 V, power 30 VA</p>
1	0 784 45	<p>Mechanical keycard switches Operates via contact with ISO card or key fob Cat.No 089806 Contact capacity: - 110 V, power 15 VA - 230 V, power 30 VA</p>
10	0 898 06	<p> 15 Key fob Supplied complete with a label holder for individual hotel identification</p>
5	0 770 47	<p>Hotel bedroom indicators Indicator lamp and bell push Enables the resident to inform hotel staff of the room status Two settings are possible: - do not disturb - please clean the room Installed in the corridor, displays calls Supplied with lamps</p>
5	0 770 48	<p> Allows the user to select the desired setting Supplied with lamp Cat.No 0 676 68 (p. 877)</p>

Pack	Cat.Nos	Shaver socket IP 24 - IK 04
1	0 775 86	<p>Conform to EN 60742 and EN 61558-2 Power supply 230 V~ - 50/60 Hz and 1 output 120/220 V~ Connection via automatic terminals Equipped with a circuit separation transformer to isolate the user from the mains supply Protected against overloads and short circuits by built-in thermal relay limiting the available power to 20 VA Insertion of the plug activates the power supply to the transformer With integrated support For flush mounting 2 gang boxes only, 40 mm deep 5 modules</p>