

Your usual Sales office www.legrand.com

Product Environmental Profile

RJ 45 SOCKET ARTEOR Cat6 Cat5e FTP UTP 2 MOD





■ LEGRAND'S ENVIRONMENTAL COMMITMENTS

- Incorporate environmental management into our industrial sites
- Of all Legrand sites worldwide, over 85% are ISO 14001-certified (sites belonging to the Group for more than five years).
- Offer our customers environmentally friendly solutions

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations

• Involve the environment in product design and provide informations in compliance with ISO 14025

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



■ REFERENCE PRODUCT **■**

Function	Connect a connection point for 10 years (reference life) with a 25 % utilization rate for a copper telecom accessory for a Tertiary LAN application.					
Reference Product	legrand					
	Cat.Nos 5 723 16 - 5 760 03 - 5 752 10					
	RJ 45 SOCKET ARTEOR Cat6 Cat5e FTP UTP 2 MOD.					

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



■ PRODUCTS CONCERNED ■

The environmental data is representative of the following products:

Catalogue	Numbers
oututogue	ITUILIDEID

- 5 723 14
- 5 723 15
- 5 710 59
- 5 728 155 728 14
- 5 728 16
- 5 700 59
- 5 713 02
- 5 713 12
- 5 713 22



Your usual Sales office www.legrand.com

Product Environmental Profile

RJ 45 SOCKET ARTEOR Cat6 Cat5e FTP UTP 2 MOD





■ CONSTITUENT MATERIALS I

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU.

Total weight of	
Reference Product	195 g (all packaging included)

Plastics as % of weight		Metals as % of weight		Other as % of weight		
PC	23.3 %	Steel	17.1 %	Electronic card	0.4 %	
PP	3.5 %	Copper alloys	0.5 %			
PET	1.5 %	Other metal	< 0.1 %			
РВТ	0.6 %					
PA	0.2 %					
		Packaging as % of weight			·	
PE	1.0 %			Wood	33.0 %	
PP	0.5 %			Paper	18.3 %	
Total plastics	30.6 %	Total metals	17.6 %	Total others	51.7 %	

Estimated recycled material content: 17 % by mass.



■ MANUFACTURE ■■■

This Reference Product comes from sites that have received ISO14001 certification.



■ DISTRIBUTION ■

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 116 km by road, 6007 km by boat and 6317 km by plane from our warehouse to the local point of distribution into the market in all around the world.

Packaging is compliant with applicable regulation. At their end of life, its recyclability rate is 94 % (in % of packaging weight).



■ INSTALLATION ■

For the installation of the product, only standard tools are needed.



USF

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.





Product Environmental Profile

RJ 45 SOCKET ARTEOR Cat6 Cat5e FTP UTP 2 MOD





■ END OF LIFE I

The product end-of-life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse. For European market, this product falls within the scope of the WEEE directive (2012/19/EU). Therefore it must be processed through local WEEE recycling/recovery channels.

• Extended producer responsability:

The sale of this product is subject to a contribution to eco-organisations in each country responsible for managing end-of-life products in the field of application of the European Waste Electronic and Electrical Equipment Directive.

• Recyclability rate:

Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 96 %. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for the end of life of this product.

Separated into:

plastic materials (excluding packaging)
metal materials (excluding packaging)
other materials (excluding packaging)
packaging (all types of materials)
: 50 %



■ ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end-of-life. It is representative from worlwide marketed products.

For each phase, the following modelling elements were taken in account:

Manufacture	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.			
Distribution	Transport between the last Group distribution centre and an average delivery point in the sales area.			
Installation	The end of life of the packaging.			
Use	 Product category: Socket RJ 45 - PSR-0005-ed2-EN-2016 03 29 - 3.8.1.2. Copper Telecom accessories. Use scenario: Socket RJ 45 - PSR-0005-ed2-EN-2016 03 29 - 3.8.2.2 Usage scenario: LAN tertiary, non continuous operation for 10 years, cat 6 for 25 % of the time. This time modeling is not requirement of minimum durability. Energy model: Electricity Mix; China - 2009. 			
End of life	The default end of life scenario maximizing the impacts.			
Software and database used	EIME & database CODDE-2018-11			



Your usual Sales office www.legrand.com

Product Environmental Profile

RJ 45 SOCKET ARTEOR Cat6 Cat5e FTP UTP 2 MOD





■ SELECTION OF ENVIRONMENTAL IMPACTS ■

	Total for l	_ife cycle	Raw material a manufact		Distributi	on	Installatio	on	Use		End of life	•
Global warming	3.21E+00	kgCO ₂ eq.	5.58E-01	17 %	2.59E+00	81 %	5.77E-03	< 1 %	5.12E-02	2 %	9.11E-03	< 1 %
Ozone depletion	3.23E-08	kgCFC-11 eq.	2.77E-08	86 %	3.96E-09	12 %	3.07E-11	< 1 %	4.08E-10	1 %	1.90E-10	< 1 %
Acidification of soils and water	9.51E-03	kgSO ₂ eq.	1.20E-03	13 %	8.20E-03	86 %	2.66E-05	< 1 %	5.55E-05	< 1 %	3.56E-05	< 1 %
Water eutrophication	4.30E-03	kg(PO ₄)³- eq.	2.47E-03	57 %	1.76E-03	41 %	1.66E-05	< 1 %	1.47E-05	< 1 %	4.56E-05	1 %
Photochemical ozone formation	6.90E-04	kgC ₂ H ₄ eq.	1.19E-04	17 %	5.60E-04	81 %	1.89E-06	< 1 %	6.56E-06	< 1 %	2.75E-06	< 1 %
Depletion of abiotic resources - elements	2.39E-05	kgSb eq.	2.38E-05	100 %	1.03E-07	< 1 %	2.47E-10	< 1 %	2.25E-10	< 1 %	5.37E-10	< 1 %
Total use of primary energy	4.98E+01	МЛ	1.22E+01	24 %	3.66E+01	73 %	7.96E-02	< 1 %	8.38E-01	2 %	1.03E-01	< 1 %
Net use of fresh water	4.37E-02	m³	4.34E-02	99 %	2.42E-04	< 1 %	1.29E-06	< 1 %	5.72E-05	< 1 %	6.64E-06	< 1 %
Depletion of abiotic resources - fossil fuels	4.42E+01	МЛ	6.82E+00	15 %	3.64E+01	82 %	7.80E-02	< 1 %	7.74E-01	2 %	9.42E-02	< 1 %
Water pollution	5.88E+02	m³	1.57E+02	27 %	4.27E+02	73 %	9.09E-01	< 1 %	2.55E+00	< 1 %	1.10E+00	< 1 %
Air pollution	1.07E+02	m³	4.72E+01	44 %	5.33E+01	50 %	4.53E-01	< 1 %	5.31E+00	5 %	9.43E-01	< 1 %

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website. To know the values of the environmental impacts of the products concerned other than the reference product, multiply the values of environmental indicators by the following corresponding factors:

The Reference Product: 5 723 16 RJ 45 socket ARTEOR Category 6 FTP - 9 contacts 2 modules - white Coefficient of extrapolation of environmental indicators						
Associated References	Manufacturing	Distribution	Installation	Use	End of Line	
5 723 14	1	1	1	1	1	
5 723 15	ı	l I	l l	ļ ,	'	
5 710 59						
5 728 14	1.1	1	1	1	1	
5 700 59						
5 728 15						
5 728 16						

Registration N°: LGRP-00946-V01.01-EN	Drafting rules: «PEP-PCR-ed3-EN-2015 04 02» Supplemented by «PSR-0005-ed2-2016 03 29»
Verifier accreditation N°: VH02	Information and reference documents: www.pep-ecopassport.org
Date of issue: 09-2019	Validity period: 5 years
Independent verification of the declaration and data, in a Internal \square External \square	compliance with ISO 14025 : 2010
The PCR review was conducted by a panel of experts cha	aired by Philippe Osset (SOLINNEN)
PEP are compliant with XP C08-100-1 : 2014 The elements of the present PEP cannot be compared w	with elements from another program
Document in compliance with ISO 14025 : 2010: «Enviror Type III environmental declarations»	
Environmental data in alignment with EN 15804: 2012 +	A1 : 2013