

FR\_708385

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

# **CB TEST CERTIFICATE Product** Portable socket-outlet Rewirable portable socket-outlets Name and address of the applicant **LEGRAND FRANCE** 128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY 87045 LIMOGES CEDEX - FRANCE LEGRAND FRANCE Name and address of the manufacturer 128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY 87045 LIMOGES CEDEX - FRANCE Name and address of the factory NINGBO BANMEN ELECTRIC APPLIANCE CO., LTD East Industrial Zone, Guanhaiwei Cixi City 315314 ZHEJIANG PROVINCE - CHINA Note: When more than one factory, please report on page 2 ☐ Additional Information on page 2 Ratings and principal characteristics See Annex Trademark / Brand (if any) legrand Customer's Testing Facility (CTF) Stage used Model / Type Ref. RNS10X series 0 494 96, 0 494 97, 0 494 98, 0 494 99 Additional information (if necessary may also be ☐ Additional Information on page 2 reported on page 2) A sample of the product was tested and found to IEC 60884-1:2002+A1:2006+A2:2013 be in conformity with As shown in the Test Report Ref. No. which ABND-ESH-P19121104 forms part of this Certificate This CB Test Certificate is issued by the National Certification Body



LCIE – Laboratoire Central des Industries Electriques 33, avenue du Général Leclerc – BP8 FR 92 266 Fontenay aux Roses Cedex

www.lcie.fr

Date: 28/04/2020

LABORATOIRE CENTRAL DES INDUSTRIES ELECTRIQUES S.A.S au capital de 15.745.984 €

8.A.S au capital de 15.745.984 €
RCS Nanterre B 408 363 174
33 avenue du Général globerture: Julien Gauthier
F - 92266 FONTENAY AUX ROSES Certification Officer



FR\_708385

## **ANNEX**

#### **Technical characteristics**

Model	Type Reference	Number of socket- outlets	Color of enclosure
RNS10X	0 494 96	3	white/grey
	0 494 97	4	white/grey
	0 494 98	5	white/grey
	0 494 99	6	white/grey

### **RATING AND MAIN CHARACTERISTICS**

## **CLASSIFICATION**

standard Sheet:	Standard Sheet V of CEE 7	
rated current (A)	16A	
rated load (W)	3680W	
rated voltage (V)	250V	
household voltage (V)	230V	
degree of protection	IP20	
provision for earthing	with earthing contact	
method of connecting the cable	rewirable	
type of terminals	screw-type	
type of connections	-	
colour	white/grey	
socket-outlets		
multiple socket-outlets number of socket-outlets	16A: 3 to 6	
degree of protection against electric shock	normal protection	
existence of shutters	with shutters	
method of application - mounting	portable type	
method of installation	-	



LCIE – Laboratoire Central des Industries Electriques 33, avenue du Général Leclerc – BP8 FR 92 266 Fontenay aux Roses Cedex

www.lcie.fr

Date: 28/04/2020

S.A.S au capital de 15.745.984 €
RCS Nanterre B 408 363 174

1 33 avenue du Général Gualeture: Julien Gauthier
F - 92266 FONTENAY AUX ROSES Certification Officer